



## Safety Data Sheet

**24 Hour Emergency Phone Numbers**  
**Medical/Poison Control:**  
**In U.S.: Call 1-800-222-1222**

**Outside U.S.: Call your local poison control center**

**Transportation/National Response Center:**

**1-800-535-5053**  
**1-352-323-3500**

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

### 1. Identification

<b>Product Name:</b>	Orange Peel Solvent Based Spray Texture	<b>Revision Date:</b>	1/1/0001
<b>Product UPC Number:</b>	070798500068	<b>Supersedes Date:</b>	9/2/2022
<b>Manufactured For</b>	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)  www.dap.com  Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222	<b>Product Use/Class:</b>	Spackling Compound
		<b>SDS No:</b>	4900104
		<b>Preparer:</b>	Regulatory and Environmental Affairs

### 2. Hazards Identification

**EMERGENCY OVERVIEW:** CAUTION! Removal of this product after use or by dry sanding will generate dust and exposure to this dust may be irritating to the eyes, ears, nose and mouth. Contents under pressure. Do not puncture can. Exposure to temperatures above 120 °F may cause can to rupture.

#### GHS Classification

Carc. 1A, Fl Aer, 1, Gas under Pressure, Comp. Gas

#### Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

46% of the mixture consists of ingredients of unknown acute toxicity

**GHS HAZARD STATEMENTS**

Flammable Aerosol, category 1	H222	Extremely flammable aerosol.
Compressed Gas	H280	Contains gas under pressure; may explode if heated.
Carcinogenicity, category 1A	H350	May cause cancer.

**GHS LABEL PRECAUTIONARY STATEMENTS**

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
P501	Dispose of contents/container.

**3. Composition/Information on Ingredients**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
n-Butyl acetate	123-86-4	10-30	No Information	No Information
Sodium Potassium aluminosilicate	37244-96-5	10-30	No Information	No Information
Stoddard solvent	8052-41-3	5-10	No Information	No Information
Propane	74-98-6	3-7	GHS07	H332-336
Methyl ethyl ketone (MEK)	78-93-3	1-5	GHS07	H332
Titanium dioxide	13463-67-7	1-5	GHS07-GHS08	H335-351
Isobutane	75-28-5	1-5	GHS02-GHS07	H220-332-336
Acetone	67-64-1	0.5-1.5	No Information	No Information
Respirable crystalline silica	14808-60-7	0.1-1.0	GHS07-GHS08	H332-350-370-372

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

**4. First-aid Measures**

**FIRST AID - INHALATION:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

**FIRST AID - EYE CONTACT:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

**FIRST AID - INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

**5. Fire-fighting Measures**

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Containers may explode if exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

**6. Accidental Release Measures**

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

## 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Remove all sources of ignition. Make sure nozzle is directed away from yourself prior to discharge. Keep away from open flames, hot surfaces and sources of ignition. Avoid heat, sparks and open flames. Wear appropriate personal protection. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Do not breathe dust. Removal of this product after use will result in the generation of Dust. If dry-sanded, exposure to dust may result in the build-up of material in eyes, ears, nose, and mouth which may cause irritation. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion. Wash thoroughly after handling.

**STORAGE:** Store away from sources of ignition and heat. Keep away from heat and sources of ignition. Avoid excessive heat and freezing. Protect material from direct sunlight. Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers. Keep containers tightly closed.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
n-Butyl acetate	50 ppm TWA Butyl acetates, all isomers	150 ppm STEL Butyl acetates, all isomers	150 ppm TWA, 710 N.E. mg/m <sup>3</sup> TWA	
Sodium Potassium aluminosilicate	N.E.	N.E.	N.E.	N.E.
Stoddard solvent	100 ppm TWA	N.E.	500 ppm TWA, 2900 mg/m <sup>3</sup> TWA	N.E.
Propane	See Appendix F: Minimal Oxygen Content, explosion hazard	N.E.	1000 ppm TWA, 1800 mg/m <sup>3</sup> TWA	N.E.
Methyl ethyl ketone (MEK)	200 ppm TWA	300 ppm STEL	200 ppm TWA, 590 N.E. mg/m <sup>3</sup> TWA	
Titanium dioxide	0.2 mg/m <sup>3</sup> TWA nanoscale respirable particulate matter, 2.5 mg/m <sup>3</sup> TWA finescale respirable particulate matter	N.E.	15 mg/m <sup>3</sup> TWA total dust	N.E.
Isobutane	N.E.	1000 ppm STEL explosion hazard Butane, isomers	N.E.	N.E.
Acetone	250 ppm TWA	500 ppm STEL	1000 ppm TWA, 2400 mg/m <sup>3</sup> TWA	N.E.
Respirable crystalline silica	0.025 mg/m <sup>3</sup> TWA respirable particulate matter	N.E.	50 µg/m <sup>3</sup> TWA Respirable crystalline silica	N.E.

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. Use an approved NIOSH/OSHA respirator if dry sanded. National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m<sup>3</sup>) as determined by a full shift sample up to 10-hour work shift. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



**SKIN PROTECTION:** Wear protective gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



**OTHER PROTECTIVE EQUIPMENT:** Not required under normal use.



**HYGIENIC PRACTICES:** Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	Red	<b>Physical State:</b>	Aerosol
<b>Odor:</b>	Solvent	<b>Odor Threshold:</b>	Not Established
<b>Density, g/cm<sup>3</sup>:</b>	1.27 - 1.27	<b>pH:</b>	Not Applicable
<b>Freeze Point, °C:</b>	Not Established	<b>Viscosity (mPa.s):</b>	Not Applicable
<b>Solubility in Water:</b>	Not Established	<b>Partition Coeff., n-octanol/water:</b>	Not Established
<b>Decomposition Temperature, °C:</b>	Not Established	<b>Explosive Limits, %:</b>	N.E. - N.E.
<b>Boiling Range, °C:</b>	N.A. - N.A.	<b>Auto-Ignition Temperature, °C</b>	Not Established
<b>Flash Point, °C:</b>	N.A.	<b>Vapor Pressure, mmHg:</b>	Not Established
<b>Evaporation Rate:</b>	Faster Than n-Butyl Acetate	<b>Flash Method:</b>	Not Applicable
<b>Vapor Density:</b>	Heavier Than Air	<b>Flammability, NFPA:</b>	Aerosol Level I
<b>Combustible Dust:</b>	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Do not burn or use a cutting torch on the empty container. Excessive heat or flames, incompatible substances. Excessive heat and freezing. Keep away from open flames, hot surfaces and sources of ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**INCOMPATIBILITY:** Open flames, hot surfaces and sources of ignition. Incompatible with strong bases and oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Above 1450 degree C: SO<sub>2</sub> and CaO.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Dust from dry sanding may cause eye, skin, nose, throat and respiratory tract irritation.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion may result in obstruction when material hardens.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** The International Agency for Research on Cancer (IARC) has determined that crystalline silica in the form of quartz or cristobalite that is inhaled from occupational sources is carcinogenic to humans (Group 1- carcinogenic to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (published in June 1997) in

conjunction with the use of these materials. The National Toxicology Program (NTP) classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (Group A2). Breathing dust containing respirable crystalline silica may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have the following serious chronic health effects: Excessive inhalation of respirable dust can cause pneumoconiosis, a respiratory disease, which can result in delayed, progressive, disabling and sometimes fatal lung injury. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Smoking exacerbates this disease. Individuals with pneumoconiosis are predisposed to develop tuberculosis. There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) and kidney disease. Prolonged or repeated inhalation of dust may cause lung damage. Constituents of this product include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Inhalation, Eye Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
123-86-4	n-Butyl acetate	14130 mg/kg Rat	>17600 mg/kg Rabbit	> 21 mg/L Rat
37244-96-5	Sodium Potassium alumino silicate	N.I.	N.I.	N.I.
8052-41-3	Stoddard solvent	>7000 mg/kg Rat	>2000 mg/kg Rabbit	21 mg/L Rat
74-98-6	Propane	Not an exposure route	Not an exposure route	N.I.
78-93-3	Methyl ethyl ketone (MEK)	2483 mg/kg Rat	5000 mg/kg Rabbit	34.5 mg/l Rat
13463-67-7	Titanium dioxide	>10000 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L
75-28-5	Isobutane	N.I.	N.I.	N.I.
67-64-1	Acetone	5250 mg/kg mouse	>15688 mg/kg rabbit	50 mg/L Rat
14808-60-7	Respirable crystalline silica	N.I.	N.I.	N.I.

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Residues and spilled material are hazardous waste due to ignitability. Contents under pressure. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Do not flush into surface water or sanitary sewer system. Do not empty into drains. Do not re-use empty containers. The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture, or weld on or near this container. Before disposing of containers, relieve container of any remaining product and pressure. Empty cylinders, once relieved of all pressure, can be disposed of as non-hazardous waste.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

## 14. Transport Information

DOT UN/NA Number: UN1950  
DOT Proper Shipping Name: Aerosols, flammable  
DOT Technical Name: N.A.  
DOT Hazard Class: 2.1 Flammable gas  
Hazard SubClass: N.A.  
Packing Group: N.A.

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Gas under pressure, Carcinogenicity

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No SARA 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## 16. Other Information

Revision Date: 2/9/2023 Supersedes Date: 9/2/2022

Reason for revision: Product Composition Changed  
Substance Regulatory CAS Number Changed  
Substance Hazardous Flag Changed  
Substance Hazard Threshold % Changed  
Substance and/or Product Properties Changed in Section(s):  
02 - Hazards Identification  
09 - Physical & Chemical Information  
15 - Regulatory Information  
16 - Other Information  
Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

#### HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
2	4	0	X

VOC Less Water Less Exempt Solvent, g/L: 469.2

VOC Material, g/L: 461

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 36.31

VOC Actual, Wt/Wt%: 36.4

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H220	Extremely flammable gas.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H351	Suspected of causing cancer.
H370	Causes damage to organs . Classified Category 1 Substances that produced significant toxicity in humans and evidence to produce significant toxicity with single exposure. Cell death, adverse change in biochemistry, haematology or urinalysis parameters, Central or peripheral nervous system and effects senses. multifocal or diffuse necrosis, fibrosis or granuloma formation in organs.
H372	Causes damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

We believe the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.