说明书

版式设计要求:

140mm

- 1. 字体: 标题为Myriad Pro SemiBold, 内容为 Myriad Pro light;
- 2. 上下页边距为9mm,左右边距为8mm;;
- 3. 标注说明书长宽尺寸, 单位mm.

Waterdrôp

Model: WDP-F09

The WDP-F09 is a compatible replacement for the following water filters:

Whirlpool[®] filters

8171414, 8171414R, 8171413, 8171413R, 2204324, 2204326, 2206039, 2206048, WFI-NL200, WFI-NLC200, NL200, NLC200, WFI-NLCS200, NLCS200, EDR8D1 KitchenAid® filters

8171788, 8171787, 2213384

Sears[®] / Kenmore[®] filters

9002, 469002, 46-9002, 9002P, 04609002000



Tested and Certified by NSF International against NSF/ANSI Standards 42, 53 and 401 in model EFF-6009S for the reduction of the claims specified on the Performance Data Sheet, and to NSF/ANSI 372 (≤0.25% lead).

Installation instructions

Before installation:

shown in the graphic.

- Shut off the cold-water supply to the refrigerator before installation. Turn on the refrigerator water dispenser to release water pressure, letting water drain from the pipe completely.
- It is normal for black carbon fines (particles) to appear on the outside of your filter. This happens when the filter is jarred in shipping. It is safe to simply wipe it off.
- The filter connectors are larger to prevent leaks. You might have to twist the filter hard to make sure
 the connection is secure.

1. Locate existing filter and remove it by turning it counter-clockwise as

and sanitary end-cap from the new filter.

2. Holding the new filter in your hands, carefully remove the packaging



3. Apply slight upward pressure and rotate the filter clockwise. Ensure filter is fully installed in refrigerator head a full 1/4 turn. This is required to activate the internal valve inside the refrigerator. If the filter is not turned a full 1/4 turn the valve will not fully open and may cause the water flow to be slow, or even cause the valve to make a chattering noise during use.

4. Dispense water into a glass looking for good water flow. If flow is slow, remove and reinstall filter ensuring that the filter is turned a full 1/4 turn. **Note:** Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.

Resetting your filter indicator:

Note: These are the most common filter reset instructions. If the instructions don't work for your refrigerator brand, see the documentation that came with your refrigerator.

Refrigerator brand	Instructions
Whirlpool® systems	Press the light switch five times within ten seconds. If the fridge has a filter button, press and hold it for 5-10 seconds.
Kenmore [®] systems	The filter reset for Kenmore refrigerators varies by model. See the documentation that came with your refrigerator.

Storage and maintenance:

- Replace your filter every 6 months or 300 gallons to prevent bacteria and fungus growth in your filter, supply lines, and storage tank.
- Keep your unused filters in a cool, dark, and dry place until you need them.
- If you do not use your water dispenser for more than four days, run two gallons of water before using it to prevent bad tasting water.

Frequently asked questions:

Q: Why is it difficult to twist the new filter into the filter housing?

- A: The connector may expand because of water pressure. Therefore, it is recommended you push the new filter in with a little bit of force, but not too hard. Then turn it clockwise.
 Q: Do I need to flush the filter after installation?
- A: After installation, it is highly recommended you run water for a few minutes before using. Water
- filters are made from advanced coconut carbon block, so there are some carbon fines in the filter. Flushing removes the carbon fines to produce clean water.

210mm

Q: Must the filter be changed every 6 months?

A: Yes, you must replace the filter every six months or sooner if water flow is reduced or if there is heavy sediment / rust present. Over-used filters will degrade the filtration performance.

▲ Warning:

To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and instructions. This filter unit must be replaced every 300 gallons or 6 months. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product. Whirlpool* is a registered trademark of Whirlpool USA.

Whirlpool® is used for reference purposes only. KitchenAid® is a registered trademark of Whirlpool Properties, INC.

KitchenAid® is used for reference purposes only.

Kenmore® is a registered trademark of KCD IP, LLC.

Kenmore[®] is used for reference purposes only. *The service life mentioned above is subject to chlorine reduction

Actual result varies according to the local water quality.

Performance data sheet

System Model No.: **EFF-6009S** Replacement Filter Cartridge Model No.: **WDP-F09**

Operating specifications:

Operating Temperature: 33°F - 100°F/0.6°C - 38°C Working Pressure: 20 psi -100 psi/140 kPa - 689 kPa Rated Capacity: 300 gallons/1,137 litres Flow Rate: 0.5 gpm/1.9 lpm





Please scan the code to get detailded Performance Data sheet.



