

GT529-NRB Finish(B) ☐

GT529-NRC Finish(C) ☐

GT529-NRS Finish(S) ☐



Specifications

Features

- 1.8 GPM Flow Rate
- 13.5" Extended Hose Length
- Nylon Braided Hose
- 3 Function Pull-Down Sprayer (Spray, Stream, and Hydroblade™)
- Auto Align Magnetic Spray Head Docking
- 36 in Nylon Flex-Line Supply Lines
- Forward Handle Operation
- 360° Rotating Spout
- High Arc Spout
- Optional Soap Dispenser Available, Order KSD-SRD* Separately
- Optional Deckplate Available, Order 961-168* Separately
- Convert to LEED Requirements with Separate Insert: Low Flow Regulator 1.5 GPM (941-683) and 1.0 GPM (941-444)
- Pforever Seal Ceramic Disc Valve
- Pforever Warranty*



Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- NSF 61/9 Annex G (Low lead)
- Cal Green Compliant
- CEC Compliant
- ADA Compliant-ANSI A117.1 (Lever handles only)
- ASME A112.18.3 (Backflow Prevention)



Dimensions



Optional Deckplate

Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings