

Model 62 UL Listed Wire Combinations Strip Wire 1/2 in.

UL File Number E5238

Copper to Copper wire only (do not use on aluminum).

600 Volt Maximum. For use with solid or stranded combinations



1 or 2 #10	1 #18 w/1 or 2 #10	3 #16 w/1 or 2 #14 or #12	3 #14 w/1 #10
1 to 3 #12	2 #18 w/1 to 3 #16, #14, or #12	3 #16 w/1 #10 str.	3 #14 w/1 or 2 #12
1 to 5 #14	2 #18 w/1 or 2 #10	4 #16 w/1 #14 or #12	1 #12 Sol w/1 #10 Sol
1 to 6 #16	3 #18 w/1 or 2 #16, #14, #12, or	1 #14 Sol. w/1 or 2 #12	2 #12 w/1 #10
3 to 6 #18	#10	1 #14 w/1 or 2 #10	1 #16 w/1 or 2 #14 with 1 #12
1 #18 w/2 or 3 #16	4 #18 with 1 or 2 #16 or #14	1 #14 w/1 #8 Str	1 #16 w/1 to 3 #14, #12
1 #18 w/1 to 3 #14 or #12	4 #18 w/1 to 2 #12	2 #14 w/1 #12 or #10	1 #16 w/1 to 2 #10
2 #16 w/1 to 4 #14	4 #18 w/1 #10	2 #14 w/1 #8 Str or #10	1 #16 w/1 #12 w/1 #10
2 #16 w/1 to 3 #12	2 #16 with 1 #10	2 #14 w/1 #12 w/ 1 #10	2 #16 w/1 #14 w/1 to 2 #12
1 #16 w/1 to 2 #14 w/1 #10	3 #16 w/1 #12 w/1 #10	1 #14 w/1 #12 w/1 #10	2 #16 w/1 #12 w/1 #10