

SURFACE PROTECTANT

APPLICATION: Surface protection is recommended. Stir thoroughly before and occasionally during use. Apply using a brush for corners and a roller for wide areas. Only apply if surface, air, and product temperature is between 70° - 80°F. Keep from freezing. If frozen, let thaw at room temperature for 48 hours.

After shaking the primer can well, use the foam brush to paint a narrow ½" wide strip of primer at the bottom and top of your backsplash in a small 3-foot wide section. Next, working in small 3-foot sections, use the roller to apply a thin coat of primer starting at the backsplash and working your way down to the countertop surface. Move on to the next 3-foot section so the 2 sections blend while they are both still wet and repeat until the entire countertop is covered.

DRY TIME: Wait 8 hours for the primer to dry before starting Step 2. Clean your foam brush for re-use and dispose of the roller cover. After you are done, if you notice a spot that you missed, first allow the counters to dry for an hour before touching it up with the foam brush. Application at lower temperatures, in high humidity, or in poorly ventilated areas will affect dry time.

CLEAN UP & DISPOSAL: Clean equipment and paint splatters with warm, soapy water. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state, and local regulations.

WARNING! This product does contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

WARNING! Irritant. Harmful if swallowed. Contains Tetramethyl-5-decyne-4,7-diol, 2,4,7,9-(126-86-3). May produce an allergic reaction. Avoid contact with eyes. Causes serious eye irritation. May cause nose and throat irritation. Avoid breathing of dust and vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. Wear eye protection, protective gloves, and protective clothing. If you are experiencing eye watering, headache, or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA TC 23°C or equivalent) during and after application. Follow respirator manufacturer's direction for respirator use. Close container after each use. Wash hands, forearms, and face thoroughly after handling and before smoking and eating.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. All Giani products are lead free.

FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

KEEP OUT OF REACH OF CHILDREN!