

ProWax Polish[™]



PROWAX POLISH™ HOW-TO GUIDE



Coverage per Gallon: Approximately 500 Sq. Ft 2 Thin Coats Recommended **Approx. Dry Time:** 6 Hr. Recoat 24 Hr. Foot Traffic



Temperature Range:
Apply Between
60°F (16°C) and
95°F (35°C)

Tools Clean-Up: ProClean Degreaser™ and Warm Water



Note: If you have just completed sealing your concrete according to our guides and the sealer is completely dry, skip Step 1 and proceed to Step 2.

STEP 1: PREPARE SURFACE

- Sweep away loose dirt and debris.
- If reapplying wax on previously waxed floors:
 - Strip the floor when wax appears cloudy or hazy
 - Use floor stripper to remove old wax and finish (refer to Floor Wax Remover guide).

STEP 2: PROWAX POLISH™ APPLICATION

GENERAL APPLICATION:

- Use a sponge mop, microfiber push mop, or floor coater.
- Dampen applicator in warm water and wring out excess moisture.
- Start at a far corner to maintain a clear exit path.
- Wet applicator in ProWax Polish™ and apply first coat in one direction only.
- Angle applicator toward inside edge for excess wax runoff.
- Ensure thin and even application, re-dip in ProWax Polish™ as needed.Overlap each pass slightly until the floor is coated.
- Allow 6 hours between coats (two thin coats recommended).
- Test coat hardness with thumbnail; if dents or scratches, allow more curing time.
- Apply second coat in the opposite direction, following the same method.

PROFESSIONAL APPLICATION:

- Apply a minimum of 4-5 coats before burnishing to enhance shine and durability.
- Pad recommendations for burnishing with a floor machine:
- Preferred: Natural fiber pads.
- Alternatives: Tan, beige, or light blue synthetic pads
- Follow manufacturer's guidelines for machine operation and safety precautions.



MAINTENANCE

- Sweep daily using dust mop or cloth.
- Clean with a neutral pH cleaner such as ProClean Degreaser™ and mop bucket or automatic scrubber.
- Perform light cleaning to remove surface soils, stains, and maintain gloss and color.
- Spot treat high-traffic areas as needed.

CAUTION: May be harmful if swallowed or ingested. Contact with skin can cause mild irritation. Avoid contact with eyes.

Disclaimer: Direct Colors does not warranty or guarantee results (outcomes). Concrete variations or improper application may cause unintended results. Test product on an inconspicuous or small area and allow to fully cure to ensure compatibility and desired result.



