





58351-1/2




58351-B-1/4
"B" bracket
recessed 1/4"




58361-1/2




58361-3/4




58361-V-1/2
"CV" bracket
recessed 1/2"



58371-1/2




58371-3/4




58371-T-1/2
"T" bracket
recessed 1/2"



58371-V-1/2
"CV" bracket
recessed 1/2"



59361-1/2




59361-3/4



58-C-1



58-C-4



58-C-5



58-C-6



58-C-7



58-C-11



58-C-16



58-C-30

4" x 2 1/2" Utility Boxes

Cat. No.	Brkts.	Knockouts			Std. Pkg.	Wt. Per C
		Ea. Side Conduit	Ea. End Conduit	Bottom Conduit		
1½" deep—with conduit KO's—10.3 cubic inch capacity						
58351-1/2*	—	3—½"	1—½"	2—½"	50	42
58351-B-1/4	B	3—½"	1—½"	2—½"	25	60
1⅞" deep—with conduit KO's—13.0 cubic inch capacity						
58361-1/2*	—	3—½"	1—½"	2—½"	50	50
58361-3/4	—	2—¾"	1—¾"	2—¾"	50	50
58361-V-1/2*	CV	3—½"	1—½"	2—½"	50	58
2⅛" deep—with conduit KO's—14.5 cubic inch capacity						
58371-1/2*	—	3—½"	1—½"	2—½"	50	56
58371-3/4	—	2—¾"	1—¾"	2—¾"	50	56
58371-T-1/2*	T	3—½"	1—½"	2—½"	25	71
58371-V-1/2*	CV	3—½"	1—½"	2—½"	50	64

* Factory provided raised ground screw location.

4" x 2 1/2" Utility Box Extension Rings

1 3/8" deep—with conduit KO's—13.0 cubic inch capacity

Cat. No.	Knockouts		Std. Pkg.	Wt. Per C
	Ea. Side Conduit	Ea. End Conduit		
59361-1/2	3—1/2"	1—1/2"	50	41
59361-3/4	2—3/4"	1—3/4"	25	41

4" x 2 1/2" Utility Box Covers

Raised 1/4"

Cat. No.	Dia. Hole (in.)	Description	Std. Pkg.	Wgt. Per C
58-C-1	—	Blank	100	11
58-C-4	1 1/32"	For 4-wire twist-lock single flush receptacle	25	9
58-C-5	1 1/32"	For single receptacle	25	10
58-C-6	—	With 1/2" KO	25	11
58-C-7	—	For duplex flush receptacle	100	9
58-C-11	—	With 1/32" bushed hole	25	10
58-C-16	—	For single GFCI receptacle	25	9
58-C-30	—	For one toggle switch	100	10

Captivated screws