

Say goodbye to ugly caulk lines! eXact color® lets you match any color and ends the hassle of painting caulk. Simply add your water-based paint or stain to eXact color for an exact match.

For interior and exterior applications including: moulding, trim, baseboards, countertops, backsplashes, accent walls, tile, siding, windows, brick, stone, stucco, metal, plastics, and any place you need an exact match.

Shelf Life After Mixing: A minimum of 1 year.

Use only with water-based paints and stains.

Not for use in areas of high foot traffic or water submersion.

VOC: 21 g/L, <1.5% by wt. (including thickener)
pH of caulk base before use: 7.3
pH of thickener: 12.5

Contenido de VOC: 21 g/L, <1.5% en peso
(incluyendo el espesante)
pH de la base de calafateo antes de usar: 7.3
pH del espesante: 12.5.

CAUTION: Avoid contact with eyes and skin. Do not take internally. In case of eye contact, flush thoroughly with water. In case of skin contact, flush thoroughly with water. If breathed in, move person into fresh air. If swallowed, do not induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

PRECAUCIÓN: Evite el contacto con los ojos. No debe ingerirse. En caso de contacto con los ojos, enjuáguelos bien con agua. En caso de contacto con la piel, enjuáguelos bien con agua. Si se inhala, lleve a la persona al aire fresco. Si se traga, no induzca el vómito. Llame a un médico inmediatamente. MANTENGA LEJOS DEL ALCANCE DE LOS NIÑOS.

ADVERTENCIA: Cáncer y Daño Reproductivo - www.P65Warnings.ca.gov.

Limited Lifetime Warranty: For a detailed description of the warranty and exclusions, visit www.sashco.com.

Garantía de por vida limitada: Para una detallada descripción de la garantía y exclusiones, visite www.sashco.com.

INSTRUCTIONS:

Before you start

- Apply to clean surfaces.
- Application Range: 40°F to 90°F.
- Protect from water for 48 hrs. after application.
- eXact color will match paint once it has skinned over, in about 4 hrs.

INSTRUCCIONES:

Antes de comenzar


- Aplique a las superficies limpias.
- Rango de aplicación: 40°F a 90°F.
- Protección contra el agua durante 48 horas después de aplicar.
- El color exacto corresponderá a la pintura en cuanto se endurezca, dentro de 4 horas.



Step 1
Using the syringe, draw up 30 mL of paint (or 10 mL of stain) and inject into the top of the cartridge.
Use la jeringa, extraiga hasta 30 mL de pintura (o 10 mL de tinte) e inyecte dentro de arriba del cartucho.



Step 2
Screw on cap and shake the cartridge for at least 60 seconds - by hand or in a paint shaker/mixer.
Enrosque la tapa y agite el cartucho por lo menos 60 segundos - a mano o en un agitador/mezclador de pintura.




Step 3
Open the thickener and squeeze the entire contents into the cartridge.
Abra de espesante y apriete todo el contenido dentro del cartucho.




Step 4
Replace the cap and vigorously shake the cartridge for at least 60 seconds.
Reemplace la tapa y agite el cartucho vigorosamente por lo menos 60 segundos.



Step 5
Wait 30 minutes for the caulk to fully thicken.
Espere 30 minutos para que el calafateo se engruese por completo.



Step 6
Remove cap, attach the nozzle, and cut it to desired bead size then apply.
Remueva la tapa, fije la boquilla, corte al tamaño de gota deseado y aplique.



CE
EXT06-18



©2018 Sashco, Inc.
10300 E. 107th Place
Brighton, CO 80601
800-767-5656
www.sashco.com
Made in the USA
Fabricado en los EE.UU.



See back panel for cautions.
9.5 FL. OZ. (280 mL)
(when mixed)