

**Model 72B UL Listed Wire Combinations Strip Solid Wire #16 and smaller 1/2 in., all others 3/8 in.  
UL File Number E5238**

**Copper to Copper wire only (do not use on aluminum).**



**300 Volt Max - For use with solid or stranded combinations**

<b>1 #14 str.</b>	<b>1 #16 w/1 to 4 #20 or #22</b>		
<b>1 #16 str.</b>	<b>1 #16 w/1 #22 w/1 #18 or #20</b>		
<b>2 or 3 #16</b>	<b>2 #16 w/1 #18</b>		
<b>1 #18 str.</b>	<b>2 #16 w/1 or 2 #20</b>		
<b>2 to 4 #18</b>	<b>2 #16 w/1 #20 w/1 #22</b>		
<b>2 to 5 #20</b>	<b>2 #16 w/1 to 3 #22</b>		
<b>2 #22</b>	<b>1 #18 w/1 to 4 #20 or #22</b>		
<b>1 #14 w/1 #16</b>	<b>1 or 2 #18 w/1 #20 w/1 #22 2</b>		
<b>1 #14 w/1 or 2 #18</b>	<b>#18 w/1 to 3 #20 or #22</b>		
<b>1 #14 w/1 to 3 #20</b>	<b>3 #18 w/1 or 2 #20 or #22</b>		
<b>1 #14 w/1 to 4 #22</b>	<b>4 #18 w/1 #20 or #22</b>		
<b>1 #16 w/1 to 3 #18</b>	<b>3 #20 w/1 or 2 #22</b>		
<b>1 #16 w/ 1 #18 w/ 1 #20</b>	<b>4 #20 w/1 #22</b>		