



SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Identifier

Product Name ARMOR LV25

Alternate Product ID

Recommended Use of the Chemical and Restrictions on Use

Recommended use Decorative Concrete Sealer & Concrete Cure & Seal

Uses advised against No data available

Details of the Supplier of the Safety Data Sheet

Distributor Address Foundation Armor, 3 Howe Drive, Suite 2, Amherst, NH 03031

Emergency Telephone Number

Supplier phone number 866-306-0246

24 Hour emergency phone number 800-424-9300 (United States & Canada) 1-703-527-3887 (International)

SECTION 2: HAZARD(S) IDENTIFICATION

Hazard Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Liquids	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Carcinogenicity	Category 1B
Germ Cell Mutagenicity	Category 1B
Specific Target Organ Toxicity (Single Exposure) Respiratory	Category 3
Specific Target Organ Toxicity (Single Exposure) Narcotic Effects	Category 3
Aspiration Hazard	Category 1
Aquatic Hazard (Acute)	Category 2

Signal Word Danger!

Hazard Statements

H226 - Flammable liquid and vapor.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.

H340 - May cause genetic defects
H351 - Suspected of causing cancer.
H401 - Toxic to aquatic life.

Pictograms



Precautionary Statements

Prevention

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing vapors or mist.
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P284 - In case of inadequate ventilation, wear respiratory protection that meets the requirements in OSHA's Respiratory Protection Standard (29 CFR 1910.134) or regional standards.

Response

P301 + P310 + P331 - IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P332 + P313 - If skin irritation or rash occurs: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 - If exposed or concerned: Get medical advice/attention.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P370 + P378 - In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P312 - Call a poison center/doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.

Storage

P403 + P233 + P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405 - Store locked up.

Disposal

P501 - Dispose of contents/container to an approved waste disposal plant in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) Not Otherwise Classified (HNOC)

None known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Chemical Name	CAS Number	Weight Percentage
Petroleum Naphtha, Light Aromatic	64742-95-6	*
Acrylic Co-Polymer	*	*

Constituents of Petroleum Naphtha, Light Aromatic CAS No. 64742-95-6

Chemical Name	CAS Number	Weight Percentage
Trimethylbenzene, Isomers	25551-13-7	< 50
1,2,4-Trimethylbenzene	95-63-6	< 30
Cumene	98-82-8	1-3
Xylene (Mixed Isomers)	1330-20-7	1-3
Methyl Isopropyl Benzene	25155-15-1	< 2
Benzene	71-43-2	0-0.1

*The specific chemical identity and/or exact percentage of component(s) have been withheld as a trade secret.

SECTION 4: FIRST AID MEASURES

First Aid Instructions/Measures

Eye Contact

In case of contact, flush eyes with plenty of water for 15 minutes. Use fingers to ensure that eyelids are separated and that the eye is being irrigated. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Skin Contact

In case of skin contact, wash affected areas with soap and water for 15 minutes. For minor skin contact, avoid spreading material on unaffected skin. Immediately remove contaminated clothing and shoes. Destroy or thoroughly wash clothing before reuse. Destroy or thoroughly clean shoes before reuse. Get medical attention if irritation develops or persists.

Inhalation

If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not use mouth-to-mouth method if victim inhaled the substance. Get medical attention if irritation develops or persists.

Ingestion

If ingested, do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth to an unconscious person or who is having convulsions. Do not use mouth-to-mouth method if victim ingested the substance. Call a physician or Poison Control Center immediately.

Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms

Aspiration may cause pulmonary edema and pneumonitis. Can enter lungs and cause damage. May cause irritation to the mucous membranes and upper respiratory tract. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include redness, itching, stinging, tearing, redness, swelling, watering and blurred vision. Skin irritation. May cause dermatitis, redness and pain.

Indication of Any Immediate Medical Attention and Special Treatment Needed

Note to physicians

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO₂, water spray and alcohol-resistant aqueous film-forming foam.

Unsuitable Extinguishing Media

High volume water jet/stream. This method may scatter and spread fire.

Specific Fire and Explosion Hazards Arising from the Chemical

Vapors may form explosive mixtures with air. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations distant from the material handling point. During fire, gases hazardous to health may be formed. Static discharges may occur in this material.

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide, reactive hydrocarbons, irritating vapors

Special Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool surrounding fire-exposed equipment, containers, tanks and structures with water spray or stream. Take precautionary measures against static discharges.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required (see Section 8). Persons not wearing protective equipment should be excluded from the area of the spill until clean-up has been completed. Eliminate or remove all sources of ignition. Ensure adequate ventilation. Avoid breathing fumes or vapors.

Environmental Precautions

Avoid subsoil penetration. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Containment and Clean-up Measures

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for Safe Storage

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

Incompatible Materials

Stable under recommended storage conditions. Avoid strong oxidizing agents. Keep away from sources of ignition. No smoking. This material may have a low electrical conductivity and therefore may accumulate dangerous levels of static electricity. An ignitable vapor-air mixture can form inside storage tanks. The user must be sure to dissipate static charge by careful bonding and grounding of all equipment, and personnel involved in fluid transfer should conduct continuity checks to prove effectiveness of bonding and grounding.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits/Guidelines

Exposure Limits/Guidelines

Chemical Name	Result	ACGIH/OSHA
1,2,4-Trimethylbenzene (CAS 95-63-6)	STEL	No data available
	TWA	120 mg/m3
	PEL	25 ppm
1,3,5-Trimethylbenzene (CAS 108-67-8)	STEL	No data available
	TWA	No data available
	PEL	25 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	435 mg/m3
	PEL	100 ppm
Cumene (CAS 98-82-8)	STEL	No data available
	TWA	245 mg/m3
	PEL	50 ppm
Styrene (CAS 100-42-5)	STEL	40 ppm
	TWA	20 ppm
	PEL	100 ppm

Industrial Hygiene/Ventilation Measures

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Personal Protective Equipment

Respiratory protection

Ensure adequate ventilation, especially in confined areas. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. Wear appropriate breathing apparatus if air renewal is not sufficient to maintain vapor concentrations below threshold limit values.

Hand protection

Wear chemical resistant, impermeable gloves.

Eye protection

Chemical safety goggles or safety glasses with side-shields. Chemical safety goggles in combination with a full-face shield if a splash hazard exists.

Skin protection

Avoid all skin contact. Depending on the conditions of use, cover as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Where spray mist/vapor is anticipated, permeation resistant clothing is recommended.

Additional protective measures

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Emergency showers and eye wash stations should be available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance:	Transparent
Color:	Clear
Odor:	Moderate Aromatic Hydrocarbon

Odor Threshold:	Not Available
Upper/Lower Flammability Limits:	Not Available
Vapor Pressure:	Not Available
Vapor Density:	Not Available
pH:	Not Available
Relative Density:	.906 @ 70° F
Melting Point:	Not Available
Freezing Point:	Not Available
Solubility:	Insoluble
Initial Boiling Point/Range:	Not Available
Flash Point:	> 108° F
Evaporation Rate:	Not Available
Partition Coefficient: n-octanol/water:	Not Available
Auto-ignition Temperature:	Not Available
Decomposition Temperature:	Not Available
Viscosity:	Not Available
Volatile Organic Compounds (VOC):	< 700 g/L

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Material is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability

Material is stable under recommended storage conditions.

Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Suitable precautions should be utilized if using this product at temperatures above the flash point. Contact with incompatible materials.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon monoxide. Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Likely routes of exposure include inhalation by direct contact and vapor inhalation, eye contact by direct contact, skin contact by direct contact and ingestion by direct contact.

Health Effects and Symptoms

Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may cause depression of the central nervous system, nausea, headache, dizziness, drowsiness or unconsciousness. Exposure may cause serious eye irritation, including itching, burning, redness and tearing. Ingestion may result in headache, dizziness or

drowsiness. Aspiration may cause chemical pneumonitis or pulmonary edema. Exposure causes skin irritation or drying. Prolonged exposure may cause dermatitis or skin cracking.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

Mutagenicity	May cause genetic defects
Carcinogenicity	May cause cancer

Product

No data available.

Components

64742-95-6 Petroleum Naphtha, Light Aromatic

Oral	LD50: 8400 mg/kg (rat)
Dermal	LD50: > 2000 mg/kg (rabbit)
Inhalation	LC50: > 5.2 mg/L, 3400 ppm (rat) 4h

95-63-6 1,2,4-Trimethylbenzene

Oral	LD50: 5000 mg/kg (rat)
Dermal	No data available
Inhalation	LC50: 18 mg/L (rat) 4h

108-67-8 1,3,5-Trimethylbenzene

Oral	LD50: 5000 mg/kg (rat)
Dermal	No data available
Inhalation	LC50: 24 mg/L (rat) 4h

1330-20-7 Xylene

Oral	LD50: 4300 mg/kg (rat)
Dermal	> 1700 mg/kg (rabbit)
Inhalation	LC50: 47.6 g/L, 5000 ppm (rat) 4h

98-82-8 Cumene

Oral	LD50: 1400 mg/kg (rat)
Dermal	> 3160 mg/kg (rabbit)
Inhalation	LC50: 39 mg/L (rat) 4h
Carcinogenicity	Group 2B Possibly carcinogenic to humans

100-42-5 Styrene

Oral	LD50: 1000 mg/kg (rat)
Dermal	> 2000 mg/kg (rat)
Inhalation	LC50: 12 mg/L (rat) 4h
Carcinogenicity	Group 2B Possibly carcinogenic to humans

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

64742-95-6 Petroleum Naphtha, Light Aromatic

Toxicity to fish	LC50: 9.22 mg/l (Oncorhynchus Mykiss, 96h)
Toxicity to algae/aquatic plants	EC50: 3.1 mg/l, (Pseudokirchneriella Subcapitata, 72h)

Toxicity to Microorganisms
Toxicity to Crustacea

EC50: No data available
EC50: 6.14 mg/l (Daphnia Magna, 48h)

95-63-6 1,2,4-Trimethylbenzene

Toxicity to fish
Toxicity to algae/aquatic plants
Toxicity to Microorganisms
Toxicity to Crustacea

LC50: 7.72 mg/l (Pimephales Promelas, 96h flow-through)
EC50: No data available
EC50: No data available
EC50: 3.60 mg/l (Daphnia Magna, 48h)

108-67-8 1,3,5-Trimethylbenzene

Toxicity to fish
Toxicity to algae/aquatic plants
Toxicity to Microorganisms
Toxicity to Crustacea

LC50: 3.48 mg/l (Pimephales Promelas, 96h)
EC50: 25 mg/l (Alga Scenedesmus, 48h)
EC50: No data available
EC50: 50 mg/l (Daphnia Magna, 72h)

1330-20-7 Xylene

Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to algae/aquatic plants
Toxicity to Microorganisms
Toxicity to Crustacea
Toxicity to Crustacea

LC50: 13.40 mg/l (Pimephales Promelas, 96h flow-through)
LC50: 23.53-29.97 mg/l (Pimephales Promelas, 96h static)
LC50: 2.66-4.09 mg/l (Oncorhynchus Mykiss, 96h)
LC50: 19.00 mg/l (Lepomis Macrochirus, 96h)
LC50: 13.10-16.50 mg/l (Lepomis Macrochirus, 96h flow-through)
LC50: 7.71-9.59 mg/l (Lepomis Macrochirus, 96h static)
LC50: 30.26-40.75 mg/l (Poecilia reticulata, 96h static)
EC50: 72 mg/l (Pseudokirchneriella Subcapitata, 14d)
EC50: 0.0084 mg/l (24h)
EC50: 3.82 mg/l (Daphnia Magna, 48h)
EC50: 0.6 mg/l (Gammarus Lacustris, 48h)

98-82-8 Cumene

Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to algae/aquatic plants
Toxicity to Microorganisms
Toxicity to Microorganisms
Toxicity to Microorganisms
Toxicity to Microorganisms
Toxicity to Crustacea

LC50: 6.04-6.61 mg/l (Pimephales Promelas, 96h flow-through)
LC50: 4.80 mg/l (Oncorhynchus Mykiss, 96h flow-through)
LC50: 2.70 mg/l (Oncorhynchus Mykiss, 96h semi-static)
LC50: 5.10 mg/l (Poecilia Reticulata, 96h semi-static)
EC50: 2.6 mg/l (Pseudokirchneriella Subcapitata, 72h)
EC50: 0.089 mg/l (5m)
EC50: 1.10 mg/l (15m)
EC50: 1.48 mg/l (30m)
EC50: 172 mg/l (24h)
EC50: 7.9-14.1 mg/l (Daphnia Magna, 48h)

100-42-5 Styrene

Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to fish
Toxicity to algae/aquatic plants
Toxicity to Microorganisms
Toxicity to Crustacea

LC50: 4.02 mg/l (Pimephales Promelas, 96h flow-through)
LC50: 29.00 mg/l (Pimephales Promelas, 96h static)
LC50: 25.05 mg/l (Lepomis Macrochirus, 96h static)
LC50: 28.75-95.32 mg/l (Poecilia Reticulata, 96h static)
EC50: 78 mg/l (Skeletonema Costatum, 96h)
EC50: 5.4 mg/l (5m)
EC50: 4.7 mg/l (Daphnia Magna, 48h)

Additional Ecotoxicological Remarks

Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose in accordance with Federal, State, and Local laws and regulations. The generation of waste should be avoided or minimized wherever possible. Empty containers should be taken to an approved waste handling site for recycling or disposal. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Precautions

Recondition or dispose of empty container in accordance with governmental regulations. Do not reuse empty container without proper cleaning. Empty containers retain product residue (dust, liquid, vapor and/or gases) and can be dangerous. Do not heat or cut container with electric or gas torch.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping Name by Regulatory Entity

DOT - Land Transportation

Paint Related Material




*Not regulated by DOT in containers of less than 119 gallons

IMDG - Sea Transportation

Paint Related Material

IATA - Air Transport

Paint Related Material

Regulatory Information	UN Number	Class	Packaging Group	Label
DOT Classification	1263	3	III	
IMDG Classification	1263	3	III	
IATA Classification	1263	3	III	

SECTION 15: REGULATORY INFORMATION

United States Federal Regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

SARA 313

Chemical Name	CAS No.	Weight %	SARA 313 Threshold Value %
1,2,4 - Trimethylbenzene	95-63-6	5-25	1.0

Xylene	1330-20-7	0-2	1.0
Cumene	98-82-8	0-2	1.0
Styrene	100-42-5	0-1	0.1

CERCLA

Chemical Name	CAS No.	Hazardous Substances Reportable Quantity (RQ)
Xylene	1330-20-7	RQ 100 lb final RQ / RQ 45.4 kg final RQ
Cumene	98-82-8	RQ 5000 lb final RQ / RQ 2268 kg final RQ
Styrene	100-42-5	RQ 1000 lb final RQ / RQ 454 kg final RQ

Clean Water Act (CWA)

Chemical Name	CAS No.	CWA - Reportable Quantity	CWA - Hazardous Substances
Xylene	1330-20-7	100 lb	Listed
Styrene	100-42-5	1000 lb	Listed

SARA 311/312

Chronic health hazard, fire hazard

US State Regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm and Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

This product contains the following Proposition 65 chemicals:

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987

Cumene (CAS 98-82-8) Listed: April 6, 2010

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

US California Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)

Beneze (CAS 71-43-2)

Cumene (CAS 98-82-8)

Light Aromatic Solvent Naphtha (CAS 64742-95-6)

Trimethylbenzene, Isomers (CAS 25551-13-7)

Xylene (Mixed Isomers) (CAS 1330-20-7)

SECTION 16: OTHER INFORMATION

HMIS Ratings

Health - 1 Flammability - 2 Physical Hazard - 0 Personal Protection - Not Determined

NFPA Ratings

Health - 1 Flammability - 2 Instability - 0 Special Hazards - Not Determined

Issue Date, Revision Date and SDS Version Number

This information is found at the "Footer" of the Safety Data Sheet (all pages). See below.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.