

CALI[®] aqua-defy XL




CALI Aqua-Defy XL: Canyon Cove


Build Expansively

Designed with professional-grade durability, Vinyl Defy XL offers longer, broader luxury vinyl planks, perfect for fast home or commercial upgrades. A 100% waterproof construction, rapid click-lock milling, and strengthening limestone composite core make flooring easy to install and clean in any room without the need for glue, nails, or acclimation. An ultra-thick 20mil wear layer delivers scratch protection while built-in acoustic padding provides boosted sound insulation. Not one to sacrifice brawn for beauty, the XL collection also boasts rich hardwood visuals so authentic you'll wonder if you're standing on actual timber.


Available Colors




Canyon Cove



Seaswept Oak




Skyline Pine




Dover Beach




Paradise Pine




Natural Elm



Tidal Pool Pine



High Tide Elm



Island Acacia



CALI Aqua-Defy XL: High Tide Elm

Ready, Set, Get Wet

100% waterproof planks are exactly that, meaning Vinyl Defy XL can be installed in every room including kitchens, bathrooms, and basements. This also makes for easy cleaning!

Go Long

The XL collection’s longer, wider planks make rooms feel more expansive, open, and modern. Plus, broader boards mean installations go faster, saving time, money, mess, and energy.

Bad to the Bone

A backbone of limestone composite within each plank resists indentation and delivers 50% better dimensional stability (less expansion and contraction), requiring no acclimation or transition pieces.

Construction	100% Waterproof (SPC Composite)
Warranty	50 Year Residential, 15 Year Commercial
Grain	Light Wood Grain
Plank Length	60-15/64"
Plank Width	9"
Plank Thickness	4.7mm
Wear Layer	20mil./ 0.5mm
Milling	Rapid Click-Lock
Installation Type	Float, Glue
Sqft/Box	37.54
Attached Pad	1.0mm IXPE
Application	Residential, Commercial
Certification FloorScore® Certified	Certified Low VOC
Sound Rating	STC 61 & IIC 63
Radiant Heat Compatible	Yes (Up to 85°F)
Temperature Range	0°- 140°F

For the most up-to-date specification information, please visit CALIFloors.com



easy-to-clean



easy installation



pet-friendly



waterproof