

	TECHNICAL DATA	ROC-111
	RUST-OLEUM® CLEANER & DEGREASER	

DESCRIPTION AND USES

Rust-Oleum® Cleaner & Degreaser is formulated to break down oil, grease, stains, tire marks, dirt, harmful silicates and more to properly clean and prepare surfaces for coatings, paint, stains and sealers. Thoroughly cleaning the surface and removing contaminants is an essential step to ensure adhesion is achieved. Diluted Cleaner & Degreaser can be used to clean a coated surface.

Cleaner & Degreaser is suitable for use on bare concrete surfaces, including garage floors, basements, driveways, carports, patios, walkways and pool decks.

FEATURES

- Removes tough oil, grease, tire marks, dirt & stains
- Promotes adhesion of paints, stains & sealers
- Safe near plants and grass
- For interior and exterior use

PRODUCT

SKU	DESCRIPTION
301243	1 Gallon Cleaner & Degreaser

SURFACE PREPARATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT.

Newly poured concrete must cure for a minimum of 30 days prior to cleaning or coating. Proper surface preparation is critical to achieve best results. Wipe up any excess oil and grease spills. Sweep surface to remove dirt and loose contaminants.

MIXING INSTRUCTIONS

Dilute Rust-Oleum Cleaner & Degreaser 1:1 - 1 gal. (128 oz.) degreaser in 1 gal. (128 oz.) of water for general purpose cleaning. For cleaning painted floors, dilute 10:1 - 10 cups (80 oz.) degreaser and 1 cup (8 oz.) water. Stir diluted solution thoroughly. Avoid splashing.

DILUTION TABLE

Tough Stains	Full Strength
General Purpose Cleaning	1:1 Degreaser : Water
Painted Surfaces	10:1 Degreaser : Water

PRODUCT APPLICATION

Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%.

Pour diluted mixture of Rust-Oleum Cleaner & Degreaser onto the entire floor. Allow to soak into the surface for 20 minutes (longer soak times may be necessary for removal of curing compounds). Mist the surface as needed to keep it damp. Work into the surface with a stiff bristle broom. After scrubbing the floor, rinse thoroughly with water or power wash to remove all cleaner residue. Squeegee or broom excess moisture from the surface.

Re-application may be necessary for extremely dirty, stained floors, or hard to remove stains. When using to clean an already coated surface, dilute at a 10:1 ratio. Always test in an inconspicuous area prior to using on entire floor.

NOTE: If cleaner dries before rinsing, apply more cleaner, scrub and rinse.

DRY TIME

Allow to dry for 24 hours before staining, sealing or coating.

CLEAN-UP

Wash tools and equipment with soap and warm water. Properly dispose of all soiled rags and protect unused product from freezing.

WARNING! Avoid skin and eye contact. Harmful if inhaled or ingested. May cause respiratory irritation, asthma or breathing difficulties if inhaled. Keep away from heat, sparks and flame. Use only in a well ventilated area.

FIRST AID:

EYE CONTACT: In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention.

SKIN contact: In case of skin contact, wash thoroughly with soap and water. Consult a physician if rash or persistent irritation occurs. Clean any contaminated clothing before re-use.

INHALATION: If affected by inhalation of vapor or spray, remove to fresh air. If breathing difficulty persists or occurs later, consult a physician and have label information available.

INGESTION: If swallowed, rinse out mouth and drink water. Get medical attention immediately. **DO NOT INDUCE VOMITING.**

KEEP OUT OF REACH OF CHILDREN.

	TECHNICAL DATA	ROC-111
	RUST-OLEUM® CLEANER & DEGREASER	

PHYSICAL PROPERTIES

		CLEANER & DEGREASER
Composition		Sodium Metasilicate Pentahydrate
Weight	Per Gallon	8.4 lbs
	Per Liter	1.01 kg
Solids	By Weight	<5%
	By Volume	<5%
Volatile Organic Compounds		When diluted according to directions <0.5%
Practical Coverage at Recommended DFT		Covers 150-200 sq.ft./gal.
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity		Allow to dry for 24 hours before staining, sealing or coating
Shelf Life		2 Years
Flash Point		>200°F (93°C)
Safety Information		For Additional Information, See SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.