

WHITE

WHITE

WHITE

WHITE

WHITE



BASEBOARDS

WINDOWS

DOORS

MOLDING

TRIM

¡PRECAUCIÓN! Contiene etilenglicol. Úsela sólo con la ventilación adecuada. Evite el contacto con los ojos y la piel. No lo ingiere. Utilice guantes y gafas de seguridad. **En caso de emergencia,** llame a un centro de control de envenenamiento al 1-800-222-1222. Refiérase a la Hoja de datos de seguridad (SDS) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

GUARANTEE: If product fails to perform when used as directed, within one year of date of purchase, call **1-888-DAP-TIPS**, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 1-888-327-8477 o visite dap.com.

QUESTIONS?/¿PREGUNTAS?

Call/Llame al **1-888-DAP-TIPS** or visit/o visite dap.com & click on/ y pulse en "Ask the Expert."

DAP Products Inc.,
Baltimore, MD 21224

Made in the USA with U.S.
and globally sourced materials.

dap.com

ALEX FAST DRY[®]

Exceeds ASTM C834

FAST DRY LATEX CAULK PLUS SILICONE



SPRAY PAINT IMMEDIATELY

Pro Painter Formula

- **50 YEAR**
- **CRACK RESISTANT**
- **REDUCED DIRT PICK-UP**
- **WON'T SHINE THROUGH PAINT**
- **MULTI-SURFACE USE**
- **WATERPROOF SEAL**
- **EASY WATER CLEAN-UP & LOW ODOR**
- **INTERIOR/EXTERIOR**

Paint Projects

Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

10.1 fl oz (300 mL)

DAP® ALEX FAST DRY® ACRYLIC LATEX CAULK PLUS SILICONE is specifically formulated to meet the demanding needs of Professional Painters & deliver outstanding paint finish results. It can be brush painted in 20 minutes or spray painted immediately, so the job gets finished faster. This durable, flexible caulk won't crack or discolor paint & doesn't pick up dirt. It applies smoothly & easily, has outstanding adhesion to a wide variety of surfaces & provides a 100% waterproof seal.

FOR BEST RESULTS: Apply in temps. above 40°F. Do not apply when rain/freezing temps. are forecasted before full cure can occur. Do not use below waterline, for filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use foam backer rod. Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk. 2. Cut nozzle at a 45° angle to desired bead size. 3. Load into caulk gun. 4. Fill gap with caulk. 5. Smooth bead. 6. Clean up excess uncured caulk with damp sponge before it skins over. Cured caulk must be cut or scraped away. 7. Can be painted with brush or roller after 20 minutes or spray painted immediately. Paintable with latex or oil-based paints. 8. Allow 24 hours or longer for caulk to dry before exposure to water. 9. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead.

CAUTION! Contains ethylene glycol. Use in well-ventilated area. Do not get in eyes or on skin. Do not ingest. Use gloves and safety glasses. **For emergencies,** call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

NCCS Calif. ARB VOC
<1.5 wt/wt% (VOC 40 g/L)

