

Say Yes to
LOCTITE



Gap filling



Strong & durable



Dries crystal
clear



Indoor/Outdoor



Flexible

How to use:

1. Ensure the surfaces you want to bond are clean.
2. Apply a thin layer of glue to one surface. If bonding two non-porous surfaces, i.e. metal to metal, it is recommended to wet surfaces with a damp cloth before applying adhesive.
3. Press parts together. You may reposition for first 5 minutes. Wipe excess adhesive away with mineral spirit. Then, clamp or tape parts together while the adhesive cures.
4. Final strength after 24 hours.
5. After use: Keep tube in a dry and cool place.

NOTE: Not recommended for hard to bond plastics such as PE, PP, PTFE or applications with constant water immersion.

WARNING! Contains trimethoxyvinylsilane and amines. May be harmful if directly inhaled or swallowed. Prolonged or repeated skin contact may cause sensitization. Persons with previous allergic reactions to amines should avoid contact with product. Keep away from heat, sparks and flame. Do not breathe vapors. Use only in well ventilated areas. Avoid contact with eye, skin and clothing. Prolonged or repeated skin contact may cause dermatitis. Wash hands after using. Wear gloves when applying product. **DO NOT TAKE INTERNALLY.** Methanol is released during application and cure, which may cause dizziness, headache or nausea. **FIRST AID:** For eye contact flush with water for 15 minutes. Call a physician if irritation develops and persists. For skin contact, wash affected area with soap and water immediately. If affected by inhalation, move to fresh air and get medical attention. If ingested, do not induce vomiting. Call a physician or Poison Control Center immediately. **KEEP OUT OF THE REACH OF CHILDREN.**

⚠ WARNING! Cancer & Reproductive Harm. www.P65Warnings.ca.gov.

Made in Germany / Packaged in the U.S.A. ©Henkel Corporation 2025/30685677



1-800-624-7767

9:00am-4:00pm E.S.T. Monday to Friday



Henkel Corporation
One Henkel Way
Rocky Hill, CT, 06067



0 79340 64132 7