







Catalog Number: MC0408B115RGA2

Features and Ratings

- Outdoor Type 3R Enclosure
- 150A Continuous Meter Socket
- 150A Main Breaker Factory Installed
- Bus Rating: 225A Max.
- Ringless Meter Cover
- 120/240 Volts~ 1 Ph, 3 Wire, 4 Jaw
- 4 Spaces, 8 Circuits Max.
- Feed-Thru Terminals Installed
- Overhead or Underground Service
- 22,000 AIC Max. Rated (See Diagram for Details)
- RX Type Hubs Top End Wall w/Cover Plate Installed
- HC Type Hubs Bottom End Wall



VIEW SHOWN WITH DEADFRONT, COVER, AND DOOR REMOVED




Accessories

Filler Plate Cat. No. QF3 or ECQF3
Mechanical Breaker Interlock: ECSBPK09
Equipment Grounding Bars: Type ECGB
5th Jaw Assembly: EC5J2
Meter Socket Jumper: ECJS

Neutral Lug Kit	Wire Range	Torque
ECLK1-2	2/0 - #4	45 Lb-In.

Trade size (in)	Catalog number
<i>RX Type Hub (top endwall)</i>	
1 1/4"	EC38597
1 1/2"	EC38598
2"	EC38599
2 1/2"	EC38600
<i>HC Type Hub (bottom endwall)</i>	
2"	ECHC200
2 1/2"	ECHC250
3"	ECHC300

Schematic, Torques & Wire Sizes



Terminal	Wire Size	Torque
A1, B1	350 kcmil - #6	250 lb-in
N1, N2	300 kcmil - #4	250 lb-in
A2, B2	300 kcmil - #4	250 lb-in
Branch Breaker Terminals	See Markings on Breaker	
Neutral Bar	#10 - #14 CU	20 lb-in
	#10 - #12 AL	20 lb-in
	#8	25 lb-in
Ground Conductors Only	#6 - #4	35 lb-in
	(2) or (3) #14 AWG	20 lb-in
	(2) #12-#10 AWG	20 lb-in

Maximum breaker size on left side:
60°C Wire: CU 55A, AL 40A
75°C Wire: CU 65A, AL 50A

K.O. CHART

DESIGNATION	QTY	DESCRIPTION
A	1	3", 2-1/2", 2", 1-1/2" KO with Provision for HC Type Hub
B	5	2-1/2", 2", 1-1/2", 1-1/4", 1", 3/4" KOs
C	1	1-1/4", 1", 3/4" KOs
D	2	3/4", 1/2" KOs
E	2	1/2" KO

© 2023 Copyright Siemens Industry, Inc.

SIEMENS
Siemens Industry, Inc.

Meter Load Center Combination

Description: **150A, 1 Phase, 4 Pos, 8 Ckt, Ringless, OH/UG, Feed-Thru w/Lugs**

KAM 10/26/23 DO NOT SCALE DRAWING Dwg. No. **MC0408B115RGA2**