

BALLOON LIGHT SERIES

- Over 5 Million+ Hours of Field Performance & Data!
- 10,000+ Units Sold!
- 5+ Years OEM Balloon Light Product, Design, & Manufacturing Excellence!

LED WORK LIGHT 60W KIT | 7,800 Lumens

ECONOMICAL



Long Lifespen & Energy Efficient High Performance LEDs

SMART



Remote Control with Dozens of Light Settings

SAFE



Glare-free + UL, FCC, CE, RoHs Certified

FAST <u>₹</u> Set up in 60 seconds!





MULTIPLE MOUNTING OPTIONS



C-CLAMP



EYE-BOLT

0.5 OPERATING AMPS

DIMMABLE 10-100% **BRIGHTNESS**

> **REMOTE** CONTROL

2-STAGE TRIPOD **EXTENDS TO 6FT**























FEATURES

SAFETY

- •360 Degrees of Glare-free Illumination
- •Glare-free + UL, FCC, CE, RoHs Certified
- •Safety Certifications: UL, CE, FCC, RoHs, IP42
- •Easy Operation & Deployment

SMART

- •RF Remote Control with Dozens of Brightness Level
- •Run multiple units off a Portable Battery Pack or Gas Genrator= Energy **Efficient Benefits**
- •80% Reduced C02 Emmissions with LED Lights
- •Versatile Lighting: Mount or Hang LED Balloon Light in Tents, Warehouses and more!

RELIABLE

- •3 Year Warranty on LED, Safety Certifications and Testing,
- •10,000+ Units Sold, Over 5 Million+ Hours of Field Performance & Data!

BRIGHT

- •Bright but Not Blinding! Utilizing Proprietary Performance Diffusion
- •High Performance & Reliable Samsung LEDs rated for 50,000 Hours= 12+ Years of 365 Nighttime Operation!

PORTABLE

- •Fit Dozens of Units into any Vehicle
- •Product Includes Carry Cases for Protection & Convenience
- •Lightweight & Portable Design for Recreation Setting
- •Small & Compact for Storage in Car, Truck, Boat, RV Storage

FAST

- •360 Degrees of Illumination Set up in 60 seconds!
- •Deploy Dozens of Units in Minutes

SPECIFICATIONS

LED PERFORMANCE

Product Design	Modular 8 Sided + Top Panel	Туре	Samsung
Total Wattage (W)	60W	Luminous Flux (Lumen)	7,800 Lumens
Voltage (V)	AC 110-240 V	Color Temperature (Kelvin)	5,000K
Frequency (Hz)	50/60 Hz	Color Rendering Index (CRI)	>80
Operating Amps (A)	0.5 A	Lamp Life (Hrs)	50,000 Hrs

LED DIMENSIONS & WEIGHT

Diffuser Dimensions (Inflated) $14W \times 14L \times 7H$ in LED Fixture Weight 6 lb (2.72 kg)

LED Fixture Dimensions $7W \times 7L \times 10H$ in

15 ft (457 cm) LED Power Cable

TRIPOD DIMENSIONS & WEIGHT

Tripod Dimensions (Collapsed) 2.8 ft (86 cm)

Tripod Weight 7.1 lb (3.2 kg)

Tripod Footprint 31W x 31L x 78H in

ACCESSORIES

POLAR DIAGRAM (Radius of Light Illumination with Tripod)

Tripod Dimensions (Extended)



CARRY CASES








REMOTE SAFETY CONTROL CABLE

USER MANUAL



13

6.5ft (200 cm)

20 fc OSHA - Construction Areas & Flagger Statior 30

10 fc OSHA - Construction Plants & Shop

30 fc OSHA - First Aid Stations, Infirmarie

APPLICATIONS



Website: Volterrex.com





Email: info@ismlighting.com