


Item Number: A03949

WARNING (To reduce the risk of fire, electric shock, or personal injury):


- 1. We suggest installation by a **licensed electrician**.
- 2. Please read the instruction carefully and save it as you may need it at later time.
- $3. \quad \text{Before you start, } \textbf{NEVER} \text{ attempt any work without shutting off the electricity until the work is done.} \\$
 - A) Go to the main fuse, or circuit breaker, box in your home. Place the main power switch in the "OFF" position.
 - B) Place the wall switch in the "OFF" position.
- 4. Mounting surface should be clean, dry, flat, strong enough and 1/4" larger than the canopy on all side. Any gaps between the mounting surface and canopy exceeding 3/16" should be corrected as required.
- 5. Make sure that the ceiling or wall can stand the weight of the lamp before installation.
- 6. Make sure the voltage you are using is **120V**. The maximum wattage is **40W** per bulb.
- 7. Keep the lamp away from acidic and alkaline substances in case of damaging the surface of the lamp.
- 8. When replacing bulb, you should turn off or unplug the lamp and you must wait until it is cool as bulbs get hot quickly.
- 9. The safety instructions appearing in this manual are not meant to cover all possible conditions that may occur. It must be understood that common sense, caution and care must be used with any electrical products.

IMAGE FOR FINISHED PRODUCT:



TOOLS REQUIRED (NOT INCLUDED):

Before starting assembly and installation please prepare the needed tools as below picture



Page: -1-/3


("

PARTS TYPE & OTY INCLUDING:

- (B) Mounting plate (1)
- (C) Green ground screw (1)
- (E) Back plate (1)
- (F) Screw (4)
- (G) Lid (3)
- (H) Jar (3)

ACCESSORIES & OTY ENCLOSED:

- (A) Plastic Wire Connectors (3)
- (D) Mounting screw (2)



ASSEMBLY & INSTALLATION INSTRUCTIONS:


1. Carefully remove the fixture from the carton and check that all parts and accessories are included as shown in the above illustration.

2. Turn off power

Before you start the installation, NEVER attempt any work without shutting off the electricity until the work is done.


B) Place the wall switch in the "OFF" position.

3. Unscrew the screws (F) from the back plate (E) then carefully remove the mounting plate assembly (B).



4. Attach the mounting plate assembly (B) to outlet box with mounting screws (D).

Carefully and gently pass the outlet box wires through the center of the mounting plate assembly (B).




6. Make wire connections

Connect wires as below wires connecting shown. PLEASE NOTE THAT GROUND WIRE IS BARE COPPER WIRE,

NEVER CONNECT OTHER WIRES TO GROUND WIRES.


Connect ground wires according to the below chart



Connect wires according to the below chart


Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear,Brown,Gold or Black without tracer	Clear,Brown,Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor
*Note: When parallel wires (SPT I & SPT II)	

*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)




Twist wires together with plastic wire connector (A) until tightly joined, then carefully tuck all wires into the outlet box. NOTE: be sure that no wire strands are exposed.

7. Align the holes in the back plate (E) and mounting plate (B), then attach the back plate (E) using the previously removed screws (F). Tighten until snug.



8. Install bulbs (Not included) (Please do not exceed the maximum wattage recommended on the socket.) Thread the jar (H) onto the lid (G) till tight.



9. Check everything is already installed properly, then you could turn on the light. Enjoy!

CLEANING.

To clean, wipe the fixture with a soft cloth. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

ORDERING PARTS.

Keep this sheet for future reference in case you need to order replacement parts. All parts for this fixture can be ordered from the place of purchase. Be sure to use exact wording from illustration when ordering parts.

Page: -3-/3