





## SEMI-FLUSH ASSEMBLY

- 1. Carefully unpack and identify all parts referring to illustration for parts identification.
- 2. Turn the power to the installation point OFF.
- 3.Install the tube (1) onto the coupling (2).
- 4.Install the crystal (A) and crystal (B) onto the short arm (7).
- 5.Install the crystal (A) and crystal (C) onto the long arm (9).
- 6.Install the crystal (A), crystal (B), and crystal (C) onto the arm (8).
- 7. Assemble the canopy (10) and steel washer (11) onto the nipple (6), securing with hex nut (12).
- 8.Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
- 9. Restore power to the installation point and retain this sheet for future reference.

## PENDANT ASSEMBLY

- 1. Carefully unpack and identify all parts referring to illustration for parts identification.
- 2. Turn the power to the installation point OFF.
- 3. Install the tube (1) onto the coupling (2).
- 4. Assemble the tube (4) together using the nipple (3), then attach the bottom end of tube (4), then secure the loop (5), onto the nipple (6).
- 5. Install the crystal (A) and crystal (B) onto the short arm (7).
- 6. Install the crystal (A) and crystal (C) onto the long arm (9)
- 7. Install the crystal (A) ,crystal (B), and crystal (C) onto the arm (8).
- 8. Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
- 9. Restore power to the installation point and retain this sheet for future reference.