Whirlpool Wine Cellar

PRODUCT MODEL NUMBERS

WUW35X15D	WUW35X24D
WUW55X15D	WUW55X24D

Electrical: A 115 Volt, 60 Hz., AC only, 15– or 20–amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your wine cellar be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

OPENING DIMENSIONS

Height dimensions are shown with the leveling legs extended to the minimum height.

NOTE: When leveling legs are fully extended, add 5/8" (15 mm) to the height dimensions.

If the floor of the opening is not level with the kitchen floor, shim the opening to make it level with the kitchen floor.

15" Models



Depth Dimensions	
A*	24 ⁷ /8" (63.2 cm) - w/o handle
B*	26 ⁵/ଃ" (67.7 cm) - WUW35X15DS
B1*	26 ⁷ /8" (68.2 cm) - WUW55X15DS

WUW35X15DS

WUW55X15DS



Dimensions	
А	21 ⁷ /8" (55.5 cm)
В	25 ¹ /2" (64.7 cm)
B1	25 ¹¹ / ₁₆ " (65.2 cm)
С	15" (38.0 cm)
D	34 ¹ / ₁₆ " - 34 ⁵ / ₈ " (86.5 cm - 88.0 cm)

LOCATION REQUIREMENTS

- It is recommended that you do not install the wine cellar near an oven, radiator, or other heat source.
- Do not install in a location where the temperature will fall below 55°F (13°C). For best performance, do not install the wine cellar behind a cabinet door or block the base grille.



Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice. D

34 ¹/₁₆" - 34 ⁵/₈" (86.5 cm - 88.0 cm)