



6455 Drive-Maxx™ 1000 Premium Filler & Sealer

DRIVE MAXX 1000

- Extended application range 45°F to 99°F
- Easy stir gel formula
- Fast dry, foot traffic ready in 2 hours
- Fills hairline cracks
- Vehicle ready in 24-48 hours

Black Jack Drive-Maxx 1000 is Black Jack's premier blacktop filler and sealer. Drive-Maxx 1000 renews the look of old worn driveways and contains sand particles to fill minor imperfections. Drive-Maxx 1000 provides our best protection against the elements, unmatched durability, and the best looking finish.

SURFACE PREPARATION: Newly paved asphalt surfaces must cure for a minimum of six months or a full summer season prior to application of any sealer. Driveways should be pressure washed and thoroughly cleaned/rinsed before sealcoating. All chemicals must be removed before patching and sealing.

For oil stains, apply a degreaser (or dish soap) and scrub into stained area to promote proper bonding and prevent adhesion failures.

Repair cracks/holes with Black Jack™ Speed-Fill Elastic Crack Filler. Use Black Jack™ Speed-Patch for cracks/holes larger than 1".

For larger potholes, use suitable blacktop repair patch following manufacturer's guidelines. Repaired areas must be allowed to cure following recommended product cure times.

BEFORE YOU SEAL: Turn pails upside down prior to sealcoating (ideally for 24 hours). Then use a paddle mixer to blend product to a uniform consistency before applying. A small amount of water separation in the pail is normal and should be easily blended into the sealer. Mix product occasionally throughout the application process.

This product must be applied on a sunny day when temperatures are 45°F and rising. Best results occur in warmer temperatures up to 90°F.

Do not apply if rain or overnight temperatures below 45°F are expected within 36 hours.

TOOLS: A squeegee must be used to spread the product evenly and to achieve published application rates. **Do not use a roller.** If a textured surface is desired follow up with a brush after spreading with a squeegee. Coat the entire driveway in one continuous application to prevent color shading.

APPLICATION: Two thin coats are mandatory for optimum performance. When using multiple pails, match manufacturer's codes and blend the end of one pail with the previous pail. Manufacturer's codes can be found on the pail lid.

Lightly mist the surface. Surface should be only slightly damp and should not have pooling or standing water in any area.

Working in one small section at a time, mix and pour out 1/3 of the container and spread a thin coat across the area with a squeegee removing excess product as you seal. This sealer is not recommended or warranted for use on surfaces with slopes greater than 20°.

Apply the second coat perpendicular to the first, after the first coat has cured (approx. 2 - 4 hours). Driveway must cure approx. Humid or cloudy conditions may prolong curing time. **Two thin coats are required.**

CURE TIMES: Under normal drying conditions, (temperatures above 75°F, clear sunny skies, and humidity below 35%) Drive-Maxx 1000 can be open to foot traffic in 2 hours. For vehicle traffic, you must allow 24-48 hours for product to completely cure. Humid or cloudy conditions may prolong curing time.

NOTE: Thick coats will result in uneven coverage, tracking and drying problems.

COVERAGE RATE: Approximate Coverage Rate (per coat) for 4.75 gallon pail: 350 sq/ft on smooth driveways, 300 sq/ft. on rough/worn driveways. Coverage rates vary depending upon the condition of the existing surface. A brush and/or squeegee works best, allowing the sealer to penetrate the driveway surface. Working in a small area at a time apply thin coat, brushing away any excess as you seal. Use a cross pattern of application to insure all voids are filled and sealed.

CLEAN-UP: While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner.

PRODUCT INFO & PERFORMANCE CHARACTERISTICS

Product Code	6455-9-30
Unit Size	5 gal.
Unit Dimensions	12" x 12" x 14.75"
Fill Level	4.75 gal. / 18 L
Unit Weight	49 lbs.
UPC	027134645556
Application Temperature:	45°F and rising to 99°F
Color	Brown liquid / Dries Black
Number of Coats Required	2 Uniform Coats
VOC	<10 g/L (less water & exempt)

PRECAUTIONS: Do not mix or blend this product with any other driveway products. Protective clothing and eyewear should be used during application of these products, as product may cause skin irritation. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. **CLOSE CONTAINER WHEN NOT IN USE.** Do not reuse empty containers. Dispose of in an environmentally acceptable manner, if not for yours, than for your children's sake. This container is recyclable if cleaned immediately. Do not pour excess product in drains or watercourses. Caution should be taken on linoleum floors, which may experience slight discoloration from household traffic stains, including asphalt driveway sealers. Consult your linoleum manufacturer for suggestions. **KEEP FROM FREEZING.** Do not use in drinking water or food systems.

WARRANTY AND DISCLAIMER: Gardner-Gibson warrants product to be free of material defects for a period of 10 years, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, Gardner-Gibson shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact Gardner-Gibson below to request a refund. **Must have receipt to file a claim.** There are no warranties which extend beyond the description on the face hereof. **THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GARDNER-GIBSON TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.**



WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov