

KEEP OUT OF REACH OF CHILDREN AND PETS

FIRST AID:

Contains: Proprietary Ingredients, Starch, Carbamide.

If swallowed: call a poison control center. Do not induce vomiting. Eye contact: Flush with water for at least 15 minutes holding eyelids open. Skin Contact: Wash thoroughly with soap and water.

VOC

<1 g/L

⚠ **WARNING:** This product contains Methanol which is known to the state of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

LIMITED WARRANTY

Roman Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to replacement of product, and ROMAN disclaims all liability for consequential, punitive and special damages. Conditions of use are beyond our control.

STORAGE

Avoid freezing. Keep in cool, dry place.


ROMAN
PRODUCTS, LLC
824 STATE ST. - CALUMET CITY, IL • 60409
www.romanproducts.com • 708-891-0770



Premium Grade Heavy Duty Clear Wallcovering Adhesive

234

- Superior wet tack and slip
- Longest open time
- Stir to desired consistency
- Ideal for pasting machines
- Strippable


The No. 1 Contractor Brand

5 GAL (18.9 L)

CAUTION: DO NOT TAKE INTERNALLY.
See additional cautions elsewhere on label.

RECOMMENDED FOR MOST TYPES AND WEIGHTS OF WALLCOVERINGS.

COVERAGE

Approximately 280 square feet per gallon.

For full product usage and technical data, visit: www.romanproducts.com

SURFACE PREPARATION

Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wall-board or plaster. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

APPLICATION INSTRUCTIONS

Use only when the room temperature is above 50° F. Stir to thin paste to desired consistency. DO NOT DILUTE. Apply a thin, even coat of adhesive with a paint roller, brush, or pasting machine. Apply evenly, making sure sufficient adhesive is on edges and corners. Allow proper booking time according to manufacturer's instructions.

CLEAN-UP

Immediately remove adhesive from the face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue.

736105A



0 17104 36105 0