## **CARE AND MAINTENANCE**

Always use felt pads under allarticles to prevent discoloration or softening of the lacquer. Plastic and rubber bases on items can discolor wood. Wipe up spills immediately and avoid common hazards such as hot dishes, harsh solvents and abrasives. Cleaning should be done with a soft lint free cotton cloth dampened with water or furniture polish. On highly used surfaces we recommend applying a quality paste wax which should be used on a regular basis to provide additional protection from sratches and spills. How often you apply the wax depends on how much wear the furniture receives.

## NOTICE

- \* Please make sure that you have all parts indicated before you begin assembly of this item
- \* This item should be assembled on a soft surface to prevent scratching the finish during assembly
- \* This item may require periodic tightening


## **Part List and Hardware List**

PIECE	DESCRIPTION	PICTURE	QUANTITY
Α	Тор		1X
В	Leg-1 21-1/2"	0 0	1X
С	Leg-2 18-1/2"	0 0	1X
D	Leg-3 13"	<u>/o</u>	3X
Е	Leg-4 21-1/2"		1X
F	Leg-5 23-3/5"	•	1X
H1	Washer		11X
H2	Allen bolt	M6X40mm	11X
НЗ	Allen key		1X
H4	Rubber pad		4X
H5	Rubber pad	0	3X



Model# FOX4257

Product Dimensions:Ø35-2/5"WX13-4/5"H




Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list.


If any part is missing or damaged, do not attempt to assemble the product.

Estimated Assembly Time: 10 minutes.


Tools Required for Assembly (included): Allen Key




Step 1
Attach B to A,using allen bolt and washer(H1&H2), tighten with allen key(H3)




Step 4
Attach D to C,using allen bolt and washer(H1&H2), tighten with allen key(H3)




Step 2
Attach C to A,using allen bolt and washer (H1&H2), tighten with allen key(H3)




Step 5
Attach E to D,using allen bolt and washer(H1&H2), tighten with allen key(H3)




Step 3
Attach D to B,using allen bolt and washer(H1&H2), tighten with allen key(H3)




Step 6
Attach F to D & E,using allen bolt and washer(H1&H2), tighten with allen key(H3)



Step 7
Attach D to F & B,using allen bolt and washer (H1 &H2),tighten with allen key(H3)



Step 8
Cover the holes with rupper pads(H4)



Step 9
Put the rubber pads(H5) to the bottom of legs