


Item Number: 5128744

WARNING (To reduce the risk of fire, electric shock, or personal injury):






1. We suggest installation by a **licensed electrician**.
2. Please read the instruction carefully and save it as you may need it at a later time.
3. Before you start, **NEVER** attempt any work without shutting off the electricity until the work is done. » Go to the main fuse, or circuit breaker, box in your home. Place the main power switch in the “**OFF**” position. » Place the wall switch in the “**OFF**” position.
4. Mounting surface should be clean, dry, flat, strong enough and 1/4” larger than the canopy on all sides. Any gaps between the mounting surface and canopy exceeding 3/16” should be corrected as required.
5. Make sure that the ceiling or wall can stand the weight of the lamp before installation.
6. Make sure the voltage you are using is **120V**. The maximum wattage is **Type B, Max. 40W** per bulb.
7. Keep the lamp away from acidic and alkaline substances in case of damaging the surface of the lamp.
8. When replacing bulbs, you should turn off or unplug the lamp and you must wait until it is cool as bulbs get hot quickly.
9. The safety instructions appearing in this manual are not meant to cover all possible conditions that may occur. It must be understood that common sense, caution and care must be used with any electrical products.

IMAGE FOR FINISHED PRODUCT:



**TOOLS REQUIRED
(NOT INCLUDED):**

Before starting assembly and installation please prepare the needed tools as below picture

				
Ladder	Philips Head or Flat Blade Screwdriver	Electrical Tape	Pliers	Wire Cutter/Stripper

PARTS TYPE & QTY INCLUDING:



- (C) Single bar (1) (L) Loop rod (3)
- (D) Green ground screw (1) (M) Stem (1)
- (E) Canopy (1) (N) Sockets assembly (1)
- (F) Collar ring (1) (O) Iron ring (1)
- (G) Collar loop (1) (P) Smaller glass (6)
- (H) Quick link (5) (Q) Connector-B (12)
- (I) Chain (1) (R) Bigger glass (6)
- (J) Loop (1) (S) Screw (12)
- (K) Fixture loop assembly (1) (T) Connector-A (12)

ACCESSORIES & QTY ENCLOSED:

- (A) Wire connector (3)
- (B) Mounting screw (2)

ASSEMBLY & INSTALLATION INSTRUCTIONS:

1. Carefully remove the fixture from the carton and check that all parts and accessories are included as shown in the above illustration. 2. Make pre-installation



Step A1 » Thread connector-A (T) into iron ring (O) as shown in the illustration.


Step A2 » 1) Thread connector-B (Q) into smaller glasses (P) and connector-A (T) as shown in the illustration.

2) Thread screws (S) into bigger glasses (R) and connector-B (Q).

Step A3 » Screw fixture loop assembly (K) and stem (M) together onto the top of sockets assembly (N).

Step A4 » 1) Hang loop rods (L) on fixture loop assembly (K).

2) Attach quick links (H) to loop rods (L) and iron ring (O).



Step B1 » By measuring, determine the correct number of links needed for proper hanging height. Using the chain pliers, disconnect and discard the unwanted part.

Step B2 » Attach quick link (H) to chain (I) and loop (J) on the top of fixture loop assembly (K).


Step B3 » Carefully weave the fixture wires through chain (I) in and out of every other link and stop just when you reach the top of chain (I). Gently pull the wires to ensure the wires are not stressed.

3. Turn off power

Before you start the installation, NEVER attempt any work without shutting off the electricity until the work is done. » Go to the main fuse, or circuit breaker, box in your home. Place the main power switch in the “OFF” position.

» Place the wall switch in the “OFF” position.

4. Make installation



Step C1 » Remove collar ring (F) from collar loop (G). Attach single bar (C) to the outlet box with mounting screws (B).

NOTE: the side of single bar (C) marked "GND" must face out.

Step C2 » Raise canopy (E) over collar loop (G) and screw collar ring (F) to measure a proper position. Unscrew collar ring (F) from collar loop (G) and remove canopy (E). Refer to the following note, you would know the proper position where collar loop (G) should be located.

NOTE: canopy (E) should be snug against the ceiling and collar loop (G) should be screwed enough threads (no less than 6 threads) on the pre-assembled threaded nipple for more secure hanging.

If not, adjust collar loop (G) on single bar assembly (C) by screwing collar loop (G) in or out of single bar (C) until the secure length is achieved.

Step C3 » Pass chain (I) through collar ring (F) and then through canopy (E).

Step C4 » Open quick link (H), attach quick link (H) to collar loop (G). Close quick link (H).

Pass the fixture wires through collar loop (G) to the top of the pre-assembled threaded nipple and gently pull to ensure the wires are not stressed.


Step C5 » If needed, shorten the length of fixture wires. At this point, the remaining wire length measured above single bar (C) is at least 6".

Step C6 » Make wire connections

Connect wires as below wires connection shown. **PLEASE NOTE THAT GROUND WIRE IS BARE COPPER WIRE, NEVER CONNECT OTHER WIRES TO GROUND WIRES.**

Connect ground wires according to the below chart

Connect wires according to the below chart



- ***Twist wires together with plastic wire connectors until tightly joined***
- ***Wrap each connector with approved electrical tape.***
- ***Be sure that no wire strands are exposed and then carefully tuck all wires into the outlet box.***

A

GREEN GROUND
SCREW

Step C7 » Raise canopy (E) to the ceiling and secure canopy (E) in place by tightening collar ring (F) onto collar loop (G).

Step C8 » Install bulbs (not included) (Please do not exceed the maximum wattage recommended on the socket.)

5. Check everything is already installed properly, then you could turn on the light. Enjoy!

ORDERING PARTS

Keep this sheet for future reference in case you need order replacement parts. All parts for this fixture can ordered from the place of purchase. Be sure to use exact wording from illustration when ordering parts.

CLEANING

To clean, wipe the fixture with a soft cloth. Clean glass to with a mild cleaner (such as mild and non-abrasive be soap). Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.