

Project:

Fixture Type:

Location:

Contact:

Images:



Description:

P6430-3130K9

LED Post lantern with contemporary styling and clear seeded glass. Fits 3" post (order separately). 120V AC replaceable LED module, 623 lumens, 3000K color temperature and 90+ CRI.

Specifications:

Black (-31) (powdercoat) Aluminum construction Clear Seeded glass Dimmable (See Dimming Notes) 6" of wire supplied ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79)
ССТ	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR [®] qualified



Dimensions:

Diameter: 7-1/2" Height: 15"



EAST HAVEN Post top - fitter for 3" post or pedestal mounted • Wet location listed PROGRESS LED

P6430-3130K9

Dimming Notes:

P6430-3130K9 is designed to be compatible with many Electronic Low Voltage (ELV/Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P
Lutron Nova T NTELV-300
Lutron Vierti VTELV-600
Lutron Ariadni AYCL-153P
Lutron Diva DVCL-153P
Lutron Maestro MAELV-600
Lutron spacer/system SPSELV-600
Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.