

JOB NAME:

CONTRACTOR:

DATE:

PLASTIC COIL COLLATION FOR SIDING NAILS

TYPES


Smooth



Ring



PROFIT



FUNCTION

For general construction of cement board siding, fencing, and exterior trim
Fits most 15° plastic coil siding nailers

FEATURES

Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable)
Smooth Shanks provide lower withdrawal strength when compared to ring shanks
Ring Shanks are deformed to have repeated ridges to increase withdrawal strength

CORROSION

Hot Dip Galvanized (HDG) in accordance with ASTM A153 Class D standards
300-series Stainless Steel is suitable for all marine applications
316 Stainless Steel is the recommended steel for salt water or chlorinated environments

CAUTION



Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener

TECHNICAL	Length x Dia	Penny Length	Gauge (W&M)	Head Diameter	Ring Shank Length, MIN	Nails per Coil	ASTM F1667 Bend Yield*
	1-1/2 x .092	4d	13	Ø 0.219 in	1.00 in	200	100,000 psi
	1-3/4 x .092	5d	13	Ø 0.219 in	1.00 in	200	100,000 psi
	2 x .092	6d	13	Ø 0.219 in	1.13 in	200	100,000 psi
	2-1/4 x .092	7d	13	Ø 0.219 in	1.13 in	200	100,000 psi
	2-1/2 x .092	8d	13	Ø 0.219 in	1.25 in	200	100,000 psi

* ASTM F1667 Bend Yield is a minimum average value appropriate for non-hardened products only

PRODUCT	Length x Dia	Box Count QTY	Brite sku	EG sku	HDG sku	305 SS sku	316 SS sku
Smooth	2 x .092	6000	-	-	0614135	-	-
Smooth	2-1/4 x .092	4800	-	-	0614145	-	-
Ring	1-1/2 x .092	3200	-	-	-	-	0614097S
Ring	1-3/4 x .092	3200	-	-	-	-	0614107S
Ring	2 x .092	6000	-	-	0614136	-	-
Ring	2-1/4 x .092	4800	-	-	0614146	-	-
Ring	2-1/2 x .092	3200	-	-	-	-	0614157S
Ring		4800	-	-	0614156	-	-