



Double Sided Bar LED Task Light

The NextLED® Folding Bar LED Task Light is designed for automotive maintenance or mechanical shop application. Keep this manual for the safety warning and precautions, assembly, operating, inspection, maintenance and cleaning procedures. Keep this manual and the receipt in a safe and dry place for future reference.

CAUTION: Read all instructions and warnings before operating! SAVE THESE INSTRUCTIONS!

WARNING: To avoid serious injury or death from electrical shock or fire:

1. This fixture **MUST ALWAYS BE USED IN ACCORDANCE WITH ALL ELECTRICAL AND SAFETY CODES AND ORDINANCES**, including the most recent National Electric Code (NEC) and with the Occupational Safety and Health Act (OSHA) Volume 1 on General Industry Standards and interpretations.
2. **ALWAYS** make certain that the power source conforms to the requirements on the fixture.
3. **DO NOT** inspect or service the fixture while charging.
4. **CAUTION:** Keep dry. Do not open, drop, short-circuit, incinerate, expose to temperatures higher than 140°F, or charge/use if damaged.
5. People with pacemakers should consult their physician(s) before use. Electromagnetic fields in close proximity to heart pacemaker could cause pacemaker interference or pacemaker failure.
6. This fixture is not explosive-proof, **DO NOT** use in potentially dangerous locations, such as in flammable or explosive atmospheres.
7. **NEVER** operate the light with the clear protective glass broken or removed.
8. **NEVER LOOK DIRECTLY INTO LIGHT SOURCE.** LED's are extremely bright and can damage eyes with prolonged exposure.
9. **KEEP AWAY** from heating vents, radiators, or other sources of heat.
10. **KEEP OUT OF REACH OF CHILDREN.**
11. **INTENDED FOR INDOOR AND OUTDOOR USE.**

LITHIUM BATTERY SAFETY WARNINGS

LITHIUM BATTERIES STORE A LARGE AMOUNT OF ENERGY AND WILL VENT FIRE OR EXPLODE IF MISTREATED:

1. Keep work light dry.
2. DO NOT DO ANY OF THE FOLLOWING TO BATTERY PACK:
 - a. Drop
 - b. Open
 - c. Short-circuit
 - d. Puncture
 - e. Incinerate, or
 - f. Expose to temperatures greater than 140°F.
3. Charge work light only according to these instructions

INCLUDES: LED portable work light USB Cable

Customer Service:
(877) 886-6822
www.mynextled.com
© 2024 Distributed by
Sunzi Products, Inc.
Schaumburg, IL
MADE IN CHINA

OPERATING INSTRUCTIONS

WARNING: READ ENTIRE IMPORTANT SAFETY INFORMATION SECTION at the beginning of this document including all text under subheadings therein before set up or use of this product.

NOTE: before using work light for the first time, fully charge the battery.

1. Press the button once to turn on one side of the light
2. Press the button again to switch to double sided mode
3. Press the button a third time to turn on the light on the end of the bar.
4. Press the button a final time to turn the light off.
5. When finished using the work light, store indoors away from children.

BATTERY REPLACEMENT

1. Unthread the base of the light.
2. Remove old battery, noting polarity
3. Insert a new 18650 type 3.7V, 2900mAh li-ion battery into the light, positive end first.

BATTERY CHARGING

WARNING: READ ENTIRE IMPORTANT SAFETY INFORMATION SECTION at the beginning of this document including all text under subheadings therein before set up or use of this product.

1. Insert the end of the charging cable into the charging jack, located on the side of the handle, under a cover.
2. Plug charging cable into a powered USB port.
3. The charging indicator button will light up red during charging.

After approximately 4 hours the charging indicator turns green indicating that the work light is charged and ready for use.

Unplug the charging cable.

ONE YEAR LIMITED WARRANTY



If this NextLED® product fails due to a defect in materials or workmanship, NextLED® will at its option, repair it or replace it with the same or comparable model, free of charge.

For repair or replacement under warranty, return to the retail establishment where the product was purchased.

This warranty give you specific legal rights and you may have other rights that vary from state to state.

This warranty is void if damage or defect has resulted from accident, abuse, misuse or faulty repair. In no event will NextLED® be liable for any consequential, special, incidental, or indirect damages of any kind arising out of the use or misuse of this product.

Maximum liability shall not in any case exceed the purchase price of the product including shipping. Some states do not allow the exclusion or limitation of incidental or consequential damages so the above exclusions or limitations

SPECIFICATIONS:

Maximum Output
600 Lumens (one side)
1200 lumens (both sides)

Run Time
6 hrs (one side)
3.5 hrs (both sides)

Battery
Li-ion 18650,
3.7V 2900 mAh

Input Rating
5V DC (USB-C Charging cable included, Charger not included, sold separately)

Charging Time
Approx. 4 hrs.
(based on 1A)

Water Resistance
IPX4

Your product, accessories and packaging should be discarded in an environmentally responsible way.

Illustrations, figures and photos may vary slightly due to our program of continuous product improvements.



8 47802 100235 7