

SAFETY DATA SHEET

Issue Date 05-Dec-2015 Revision Date 05-Dec-2015 Version 1

1. IDENTIFICATION

Product identifier

Product Name ELASTOMERIC EMULSION CRACK FILLER

Other means of identification

Product Code HE305 Synonyms None

Recommended use of the chemical and restrictions on use
Recommended Use Adhesives and/or sealants
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Company Phone Number 800-486-1278

Emergency Telephone CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887

CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation



Appearance viscous Physical state liquid Odor Slight

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin.

Unknown acute toxicity

15.68775515% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

<u>Mixture</u>

Chemical Name	CAS No	Weight-%
Asphalt *	8052-42-4	30 - 60
Water *	7732-18-5	30 - 60
Polyvinyl alcohol *	9002-89-5	1 - 5

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible). If symptoms persist, call a physician.

Eye contact Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial

flushing, remove any contact lenses and continue flushing for at least 15 minutes. If

symptoms persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If symptoms persist, call a physician. Wash contaminated clothing

before reuse.

Inhalation Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If

symptoms persist, call a physician.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting without

medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.

Self-protection of the first aider Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin

irritation.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Use personal protective

equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Soak up with inert absorbent material (e.g.

sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically, placing in

appropriate containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

HE305 - ELASTOMERIC EMULSION CRACK FILLER

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Handle in accordance with good

industrial hygiene and safety practice. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled

containers.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name ACGIH TLV		OSHA PEL	NIOSH IDLH
Asphalt TWA: 0.5 mg/m³ benzene soluble		-	Ceiling: 5 mg/m ³ fume 15 min
8052-42-4 aerosol fume, inhalable fraction			

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state liquid
Appearance viscous

Appearance viscous Odor Slight

ColorblackOdor thresholdNo information available

Property Values Remarks • Method

pH 6-10

Melting point / freezing point

No information available

Boiling point / boiling range > 100 °C / 212 °F Flash point > 100 °C / 212 °F

lash point> 100 °C / 212 °FTag Closed Cupvaporation rateNo information available

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Relative density 1.0 - 1.2
Water solubility dispersible

HE305 - ELASTOMERIC EMULSION CRACK FILLER

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
No information available
No information available
No information available

Kinematic viscosity > 100 mm2/s @ 40 °C

Dynamic viscosityNo information availableExplosive propertiesNot an explosiveOxidizing propertiesNot applicable

Other Information

Softening pointNo information availableMolecular weightNo information availableVOC Content (%)No information availableDensityNo information availableBulk densityNo information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

elevated temperature. Incompatible materials. Keep at >0 °C.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract.

Eye contact Severely irritating to eyes.

Skin contact Irritating to skin.

Ingestion No data available.

Chemical Name	emical Name Oral LD50		Inhalation LC50
Asphalt 8052-42-4	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	-
Water 7732-18-5	> 90 mL/kg(Rat)	-	-
Polyvinyl alcohol 9002-89-5	, , , , , , , , , , , , , , , , , , , ,		-

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin

irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

HE305 - ELASTOMERIC EMULSION CRACK FILLER

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt 8052-42-4	-	Group 2B	-	Х
Polyvinyl alcohol 9002-89-5	-	Group 3	-	-

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure Target Organs. Respiratory system. Eyes. Skin.

STOT - repeated exposure
Target Organ Effects
Aspiration hazard
No information available.
Eyes, Respiratory system, Skin.
No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 7,823.00 mg/kg

 ATEmix (dermal)
 3,158.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

99.68347 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

Chemical Name	Partition coefficient	
Asphalt 8052-42-4	6	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOTNot regulatedTDGNot regulatedIATANot regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Benzophenone - 119-61-9	Carcinogen
Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Asphalt 8052-42-4	X	X	X
Potassium hydroxide 1310-58-3	X	X	X
Quartz	X	X	Х

14808-60-7		

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 0 Instability 0 Physical and Chemical

Properties -

HMIS Health hazards 2 Flammability 0 Physical hazards 0 Personal protection X

Issue Date05-Dec-2015Revision Date05-Dec-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet