PEERLESS

Min.2 1/2" (64 mm) Clearance to Back Splash Recommended " " 1 7 7/8" (200 mm) 5" 6 11/16" . (127 mm) (170 mm) (127 mm) 6" 2" (152 mm) | PHERILI/ (50 mm) 1 1/8"~1 1/2" 1 3/8" (29~38 mm) (35 mm) Hole Size Max. Deck Thickness 27 15/16" (709 mm) 3/8" compression fitting

RP103419▲



▲ Designate proper finish suffix PSP-L-P1519LF-HA Rev. D

P1519LF-▲-HA



BATHROOM FAUCET:

- Single Handle Deck Mount
- 1 or 3 Hole Sink Applications

STANDARD SPECIFICATIONS:

- Maximum 1.0 gpm @ 60 psi, 3.8 L/min @ 414 kPa.
- Solid brass casted body.
- One or three hole mount (escutcheon optional, included).
- ceramic cartridge
- Red/Blue indicator markings
- Polymer braided flexible supply hose with 3/8" compression fitting - 27 15/16" (709mm) long
- Models have 50/50 push pop-up

WARRANTY:

 Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Lindicates compliance to ICC / ANSI A117.1
- EPA WaterSense[®]