



033

Leak Stopper® Clear Patch

Advanced Clear Sealant



- Provides “invisible” patch
- Stops leaks instantly
- Flexes to prevent cracking
- Goes on white - dries clear
- Outlasts other repairs
- Stays clear longer-won’t yellow!

WHAT IS IT? This advanced clear sealant has outstanding adhesion to a variety of surfaces, and provides a long lasting rubberized seal for almost any application. Great for sealing around decorative or visible areas where a noticeable patch is not desirable. This premium formula has outstanding UV resistance, stays clear and will not “yellow or cloud” over time like other products. It is ideal for repairing cracks in exterior or interior applications where a clear elastic seal is desired. Product is water based, and will have a cloudy white appearance when applied, but dries clear. Can be painted if needed.

USE ON THESE ROOF SURFACES: Asphalt Shingle, Slate, Tile, Metal, & Wood Shake Roofs. **ALSO SEALS TO AND AROUND:** Skylights, Wood, Glass, Stucco, Brick, Stone, Gutters, Chimneys and Siding.

WHAT IT DOES: Seals cracks to stop water leaks or seal air drafts.

WHAT IS NEEDED TO COMPLETE THE JOB? Caulking gun, trowel, gloves.

PREP THE AREA: Surfaces must be clean, dry, and free of dirt, rust and other material.

HOW TO APPLY: Apply from caulk tube, and completely fill area to be sealed.

HOW MUCH DO I NEED? Provides approximately 25 linear feet of 1/4” bead.

DO’s and DON’Ts: Apply in interior or exterior applications. Wear protective gloves.

FOR BEST RESULTS: Use product on a clear warm day when temperatures are above 65 °F. Work product to an even consistency over the area to be sealed. Use a trowel to spread over repair if needed. Product should be allowed to dry at least 24 hours before exposure to rain.

PRECAUTIONS: Protective clothing, gloves and eyewear should be used during application of these products. When transporting this product, ensure that plug is tight and tube secure and upright. Do not allow tube to tumble as this may cause plug to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. DO NOT store at temperatures above 100 °F. Seal partially used container. DO NOT reuse empty containers. Do not use in drinking water or food systems. DO NOT FREEZE. Contains petroleum based products. Keep away from heat, sparks and open flame. Seal container when not in use. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. Do not use on single ply or synthetic roofs. If there is any question regarding compatibility, test a small section first. For the longest life, store in controlled environment, 35 °F-80 °F. Do not store in direct sunlight.

HOW TO CLEAN-UP: Clean tools immediately after use with soap and water.

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc., warrants this product to give satisfactory results when our directions are followed in its use and application. Any claims made, with original sales receipt, will be based on a prorated basis. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

| AVAILABLE SIZES | | | | | | |
|-----------------|------------|--------------------|--------------------|--------------|----------|--------------|
| PRODUCT CODE | UNIT SIZE | UNIT DIMENSIONS | FILL LEVEL | UNIT WEIGHT | PACK | UPC |
| 0339-GA | 10 fl. oz. | 2" x 2" x 11.5" | 10 fl.oz. / 296 mL | 1 lb. approx | 12/crtn. | 025056033901 |
| 0338-GA | 1 qt. | 4.3" x 4.3" x 4.9" | 29 fl.oz. / 858 mL | 2.65 lb. | 12/case | 025056033802 |

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101