DKA & POWER



DESCRIPTION

Introducing the DK2 POWER OPS240 40-ton kinetic log splitter, powered by a KOHLER[®] CH270 7HP 208cc Command PRO[®] engine for outstanding performance. Equipped with an oversized reinforced steel work table, safety lockout and a clam shell quick-access body for easy use and maintenance.

The OPS240 has an 8-inch expansion wedge and an auto-retracting bearingguided ram to drive through logs up to 22 inches in diameter and up to 22

inches in length. Keep yourself safe while working with its extended stability stand and ATV locking wheels, keeping the splitter securely in place.



=EATURES

SPECIFICATION

ENGINE	KOHLER® Command PRO® CH270 7 HP 208 cc	
GEARBOX	10.7 ft/lb (14.5 Nm) gross torque	
WHEELS & TIRES	ATV-locking	
SPLITTING CAPACITY	Ø22" x 22" (L) Ø55.9 cm x 55.9 cm (L)	
WEDGE	8" (20.32 cm), steel	
H-BEAM	25" (63.5 cm) ground clearance	
CYCLE TIME	1 second	
COUPLER	2" (5.08 cm)	
DIMENSIONS	120" (L) x 37" (W) x 44" (H) 304.8 cm (L) x 94 cm (W) x 111.8 cm (H)	•
WEIGHT	616 lb (279.4 kg)	
SHIPPING DIMENSIONS	71" (L) x 27" (W) x 26" (H) 180.3 cm (L) x 68.6 cm (W) x 66 cm (H)	
SHIPPING WEIGHT	690 lb (313 kg)	
WARRANTY	3-year KOHLER® engine 1-year DK2 chassis	Constitution of

40-TON 7 HP 208 CC KINETIC HORIZONTAL LOG SPLITTER

ITEM NUMBERS

OPS240

19

UPC

826518005746

FEATURES

- Powered by a KOHLER® Command PRO® Commercial CH270 7 HP 208 cc engine
- 8" (20.32 cm) solid steel expansion wedge
- Oversized steel worktable with quadlog slides
- H-beam height sits at 25" (63.5 cm)
- Heat-treated ram with bearing glide force and auto-retraction
- Extended stability stand
- ATV-locking wheels
- Fits on a 2" (5.08 cm) hitch receiver for easy towing
- Quick-release clam shell body for easy access to interior of the unit
- Safety lock out
- Super-quick 1 second cycling time
- Includes 3-year KOHLER[®] engine and 1-year DK2 chassis warranty
- OFF-ROAD ONLY AND MAX SPEED 15MPH (24KM/H)

