

One-light Pendant

 Ceiling cord mounted • Damp location listed 

Description:

Provide a dramatic architectural lighting design to any space with this LED pendant. A smooth metal beam with a black finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings. The frame holds a polycarbonate shade in place to complete the design.

Specifications:

- Black (-031) (Painted)
- Aluminum and steel Construction
- Polycarbonate Polycarbonate Diffuser
- The frame holds a polycarbonate shade in place to complete the design.
- A smooth metal beam with a black finish suspends from the ceiling to add clean visual interest to minimalist residential or commercial settings.
- Provide a dramatic architectural lighting design to any space.
- Ideal for any hallway, foyer, kitchen, or dining room.
- Perfect for transitional, modern, or contemporary settings.
- Measures 47-1/4-inch width by 1-3/8-inch height.
- Uses one LED bulb that is included (39w max).
- Able to be fully dimmable with dimmable bulbs.
- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting Backplate for outlet box included
- 108" of wire supplied
- Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	39w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	2900/74 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Warranty	5-year limited warranty
Labels	cETLus Damp location listed Meets California Title 24 JA8-2016

P500276-031-30

Images:



Dimensions:

Width: 47-1/4"
 Depth: 1-3/4"
 Length: 47-1/4"
 Height: 1-3/8"
 Overall Ht. W/Wire: 113"

Width: 46.4325"
 Height: 0-1/16"

P500276-031-30

Dimming Notes:

P500276 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Leviton 6672

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.