

WHITE

WHITE

WHITE

WHITE

WHITE



WINDOWS

CROWN MOLDING

DOORS

TRIM

¡PRECAUCIÓN! Contiene destilados de petróleo. Utilice en un área bien ventilada. No permita el contacto con los ojos o la piel. Use guantes y gafas de seguridad. No lo ingiere. **En caso de emergencia**, llame a un centro de control de envenenamiento al 1-800-222-1222. Refiérase a la Hoja de datos de seguridad (SDS) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠️ ADVERTENCIA Cáncer y Daños al Sistema Reprodutor – www.P65warnings.ca.gov

GUARANTEE: If product fails to perform when used as directed, within one year of date of purchase, return used container & sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Ste. 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 1-888-DAP-TIPS o visite dap.com.

QUESTIONS?/¿PREGUNTAS? Call/Llame al 1-888-DAP-TIPS or visit/o visite dap.com & click on/ y pulse en "Ask the Expert."

DAP Products Inc.
Baltimore, MD 21224.

Made in the USA with U.S. and globally sourced materials.

dap.com

ALEX FLEX

Exceeds ASTM C920, Class 12.5

**PREMIUM
MOLDING &
TRIM SEALANT**



CRACKPROOF
**MAXIMUM FLEXIBILITY
& ADHESION**

- 60 YEAR
- PAINT IN 30 MINUTES
- WON'T SHINE THROUGH PAINT
- WATERPROOF SEAL
- EASY WATER CLEAN-UP
- LOW ODOR
- INTERIOR/EXTERIOR

IDEAL FOR

**WOOD, PVC &
COMPOSITE**

MOLDING

Paint Projects

Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

10.1 fl oz (300 mL)

DAP® ALEX FLEX® PREMIUM MOLDING & TRIM SEALANT is specifically formulated for use on molding & trim applications. It is a premium performance sealant that delivers maximum adhesion & flexibility for a crackproof seal. It can be painted in 30 minutes & won't shine through or discolor paint. It is easy to apply & tool, low in odor & cleans up easily with water.

SPECIFICATIONS: Exceeds ASTM C920, Class 12.5 & ASTM C834, Grade NS.

FOR BEST RESULTS: Apply in temps. above 40°F. Do not apply when rain/freezing temps. are forecasted before full cure can occur. Do not use below waterline, for filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material. Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old sealant, dirt, dust, debris & grease. 2. Cut nozzle at a 45° angle to desired bead size. 3. Load into caulk gun. 4. Fill gap with sealant. 5. Smooth bead. 6. Clean up excess uncured sealant with damp sponge before it skins over. Cured sealant must be cut or scraped away. 7. Allow 30 minutes for skin to form before painting with latex or oil-based paints. Allow additional cure time in high humidity and/or cool temperatures. 8. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead.

CAUTION! Contains petroleum distillates. Use in well-ventilated area. Do not get in eyes or on skin. Use gloves and safety glasses. Do not ingest. **In an emergency**, call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠️ WARNING Cancer & Reproductive Harm – www.P65warnings.ca.gov

NCCS Calif. ARB VOC <1.5 wt/wt%
(VOC 32 g/L)

