

**TECHNICAL DATA****RSD-57****ROCKSOLID®
DECK & PATIO CLEANER****DESCRIPTION AND USES**

RockSolid® Deck & Patio Cleaner quickly and safely restores dirty, weathered, mildew and algae stained wood to a bright, natural, like new look. This concentrated formula eliminates residual traces of old water sealers from weathered wood and invisible coating barriers such as mill glaze from new cedar, enabling proper adhesion and penetration of protective deck and patio coatings.

RockSolid Deck & Patio Cleaner is suitable for use on wood and most composite decks and may be used on wood fences and siding. It is also suitable for use on broom swept or porous concrete surfaces. Do not use on smooth or floated concrete. Not recommended for driveways, garages or other areas with vehicular traffic.

FEATURES

- Fast acting
- Removes dirt & mildew
- Removes mill glaze

PRODUCTS

SKU	Description
60635	Deck & Patio Cleaner – 1-Gallon

PRODUCT APPLICATION**MANUAL APPLICATION**

Read all instructions before beginning. When air and surface temperatures are between 50-90°F. Mix two cups of concentrate (16 oz.) with 1 gallon of water (1:8 mix ratio). Apply the cleaner to decks and patios using a deck brush or pump sprayer. Allow the cleaner to sit for 5-10 minutes. Rinse off with fresh water.

DIRECTIONS – MILL GLAZE REMOVAL

Read all instructions before beginning. By using as directed on pressure treated wood, mill glaze can be removed, which will minimize the effects of wax and water repellants that may be present in the new wood. Apply the cleaner undiluted and let sit on the surface for 5-10 minutes to penetrate. Scrub the surface thoroughly with a deck brush to remove the mill glaze. Rinse the surface with clean water to remove any residue and allow to dry. If water still beads on the surface, repeat the above steps.

CLEAN UP

Use mild soap and water.

KEEP FROM FREEZING. CLOSE CONTAINER AFTER EACH USE TO PRESERVE THE PRODUCT.

PHYSICAL PROPERTIES

Physical Properties		DECK & PATIO CLEANER
Composition		Proprietary Ingredients in a Water-based Solution
Weight	Per Gallon	8.50 lbs.
	Per Liter	1.02 kg
VOC (Weight %)		0
Practical Coverage		Up to 2,500 square feet per gallon.
Shelf Life		2 years
Flash Point		NA
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.