

## Refrigerating Appliance DOE Test Report

Report Number	181228103GZU-004
Test Laboratory Name / Address	Intertek Testing Services Shenzhen Ltd. Guangzhou Branch Room 02, & 101/E201/E301/E401/E501/E601/E701/E801 of Room 01 1-8/F., No. 7-2. Caipin Road, Science City, GETDD, Guangzhou, Guangdong, China
Applicant Name / Address	ZHONGSHAN YEHOS ELECTRICAL APPLIANCE CO., LTD. No.9, Yuanlin Rd, Nantou Town, Zhongshan, China
Manufacturing Name / Address	Same as Applicant
Product	Cooler
Brand Name	YEHOS (for model YC-100A); AVANTI (for model WCF281E3SS); WINE ENTHUSIAST (for model 264 02 30 03);Colzer (for models CZW30SS1,CZB30SS1)
Description	The product covered by this report is a household, indoor use, cord connected cooler.
Model(s) (if applicable)	YC-100A; WCF281E3SS; 264 02 30 03;CZW30SS1;CZB30SS1
Model Similarity	All the models above are identical except for the brand name and/or model designation and/or temperature control position.
Ratings	115VAC, 60Hz, 1.4A, R600a/1.52Oz
Date of receipt of sample(s)	1/Jun/2019
Date of test	2/Jun/2019 - 13/Jun/2019
Test standard(s) or criteria(s)	10 C.F.R. §430.32(aa)(1) 10 C.F.R. Appendix A to Subpart B of Part 430 Uniform Test Method for Measuring the Energy Consumption of Refrigerators, Refrigerator-Freezers, and Miscellaneous Refrigeration Products
Conclusion	The product tested complies with the Energy Efficiency Standard of DOE, starting on October 28, 2019.
Original Date	13/Jun/2019
Revised	14/Jul/2020

Prepared by:

Approved by:

Signature on file

Felix Li

Sr. Project Engineer

Signature on file

Jimmy Wang

Sr. Project Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. The test report only allows to be revised only within the report defined retention period unless standard or regulation was withdrawn or invalid. When determining the test result, measurement uncertainty has been considered. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.


**Nameplate:**



CONFORMS TO UL STD.250  
CERTIFIED TO CSA STD.C22.2 NO.63



Wine Cooler



SPECIFICATIONS	
Model	YC-100A
Total Volume	3.53 Cu. Ft.
Power	115V~60Hz
Amps	1A
Start-Up Amps	10A
Power Input	81W
Pressure High Side	105 PSI
Pressure Low Side	55 PSI
Refrigerant	R600a
Amount	1.2 oz.
Net Weight	84 lbs.
Dimensions(HxWxD)	33.5" x 15" x 23"

CAUTION: DO NOT USE EXTENSION CORD

**MADE IN CHINA**


**BUILT-IN OR FREE STANDING INSTALLATION**  
**INSTALLATION ENCASTRÉE OU AUTOPORTANTE**



CONFORMS TO UL STD.250  
CERTIFIED TO CSA STD.C22.2 NO.63

**WINEENTHUSIAST®**

Wine Cooler



SPECIFICATIONS	
Model	264 02 30 03
Total Volume	3.53 Cu. Ft.
Power	115V~60Hz
Amps	1A
Start-Up Amps	10A
Power Input	81W
Pressure High Side	105 PSI
Pressure Low Side	55 PSI
Refrigerant	R600a
Amount	1.2 oz.
Net Weight	84 lbs.
Dimensions(HxWxD)	33.5" x 15" x 23"

CAUTION: DO NOT USE EXTENSION CORD

**MADE IN CHINA**

**BUILT-IN OR FREE STANDING INSTALLATION**  
**INSTALLATION ENCASTRÉE OU AUTOPORTANTE**

**Product Information:**

Model of Unit Under Tested	YC-100A
Product Condition	Prototype
Serial No.	NA
Category	3
Product Type	Freestanding compact cooler
Refrigerant	R600a
Charge of refrigerant (Oz)	1.52
Refrigerating type	Compression-type
Condenser type	Fan forced
Condenser location	Bottom
Power Supply	Single Phase
Built-in appliances	No
Overall dimensions (mm)	Width: 380      Depth: 580      Height: 850
Defrosting type	Automatic defrost

**Critical Components:**

Name	Manufacturer/trademark	Type/model	Technical data
Compressor	HUAGUANG	EY40U6L	115V~, 60Hz, 1PH, R600a

**Measurement conditions:**

- a) General
- |                           |             |
|---------------------------|-------------|
| Test voltage (V):         | 115         |
| Test Frequency (Hz):      | 60          |
| Air velocity Range (m/s): | 0.04 – 0.16 |
- b) Ambient Temperatures of Energy Consumption Test:
- |                      |          |
|----------------------|----------|
| Dry Bulb Range (°C): | 32.2±0.6 |
|----------------------|----------|

**Volume Measurement:**

Compartment type	Description	Width (mm)	Depth (mm)	Height (mm)	Number	Volume (L)	Volume (Cu.ft)
Cooler compartment	Part 1	306	438	680	1	91.14	3.219
	Part 2	120	120	25	-1	-0.36	-0.013
	Part 3	10	410	20	-10	-0.82	-0.029
	Part 4	10	300	20	-2	-0.12	-0.004
	Part 5	306	105	170	-1	-5.46	-0.193
	Part 6	320	12	680	1	2.61	0.092
	Total:					87.0	3.07

Compartment	Volume (L)	Volume (Cu.ft)
Cooler compartment	87.0	3.07
Total volume	87	3.1
Total adjusted volume	87.0	3.07


**Energy Consumption Test:**

Sample No.	Sample 1	Sample 2	/
Location of thermostat setting of the first test	<b>Medium</b>	<b>Medium</b>	/
The average temperature in cooler compartment, °F	51.8	54.3	/
Energy expended during the first test period, kWh	0.310	0.306	/
Length of time of the first test period, min	773	762	/
Test cycle energy expended during the first test cycle during, kWh/d	0.318	0.318	/
Location of thermostat setting of the second test	<b>Warmest</b>	<b>Warmest</b>	/
The average temperature in cooler compartment, °F	62.5	65.0	/
Energy expended during the second test period, kWh	0.206	0.200	/
Length of time of the second test period, min	783	775	/
Test cycle energy expended during the second test cycle, kWh/d	0.208	0.204	/
The average per-cycle energy consumption, kWh/d (TC =55°F)	0.285	0.311	/
Annual Energy Consumption, kW·h/y	104.03	113.52	/

**Test Result Summary:**

Sampling size	2
Mean of sample	108.78
Sample standard deviation	6.710
UCL/1.1	126.13
The decided Annual Energy Consumption, kWh/Year	126.13
The decided Daily Energy Consumption, kWh/d	0.346
The rated energy consumption, kWh/Year	/
Maximum energy consumption limit, kWh/Year	180
Verdict	Pass

**Temperature measurement in cooler compartment:**



**Photos:**

**Photo 1 - Front view**



**Photo 2 - Back view**



**Photo 3** - Front view with open door



**Photo 4** - Label of compressor





## Revision Summary

[illegible]

--THE END--