


## DuraStyle Toilet wall-mounted & # 253709..92 / 253709..92 | < 14 5/8" X 24 3/8" Inch >|



Toilet wall-mounted	Dimension	Weight	Order number
washdown model, Durafix included, cUPC® listed*, WaterSense® listed			
<b>Colors</b>			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)			
<b>Variant</b>			
♣ 1.6/0.8 gpf	14 5/8" X 24 3/8" Inch	68 lb	253709..92
♣ 1.6/0.8 gpf	14 5/8" X 24 3/8" Inch	68 lb	253709..92
<b>Infobox</b>			
* Complies with following standards: ASME A112.19.2/CSA B45.1 and ASME A112.19.14, Durafix for concealed installation is included, Wall-mounted toilet is ADA compliant, when installed with a seat height of 17" - 19" from the finished floor, In-wall tank & carrier and actuator plate required for installation			
Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come. When ordering WonderGliss please add a "1" as eleventh digit to the model number.			
Noise reduction gasket			Schallschutz-Set 005090
Actuator plate A1, for toilet, plastic mechanical actuation, for surface mounted installation, dual flush, mounting frame, mounting hardware included, push rods, front plate plastic	8 1/2" x 5 3/4" Inch	0.7 lb	WD5008

## DuraStyle Toilet wall-mounted & # 253709..92 / 253709..92 | < 14 5/8" X 24 3/8" Inch >|

<p>Toilet in-wall tank &amp; carrier, Standard WaterSense® listed, For 2"x4" and 2"x6" wall installation, for toilets with a projection of &lt;= 24 5/8", adjustable feet 0" - 9 1/2", SensoWash ready, mechanical front flush actuation, includes in-wall tank, marking of filling height, dual flush, insulated against condensation, Scope of delivery, HDPE wall-mounted toilet connection bend DN 90/90, PE wall-mounted toilet connection set DN 90, wall-mounted mounting rods M12, mounting hardware included, 2 bolt caps, cUPC® listed*, Load capacity = 880 lbs</p>	23 1/4" x 45 1/4" Inch 35.3 lb	WD1022
<b>Suitable products</b>		
Toilet seat and cover removable, elongated, hinges stainless steel, without slow close,		006051
Toilet seat and cover removable, elongated, hinges stainless steel, with slow close,		006059
Toilet seat and cover removable, hinges stainless steel, without slow close,		002631
Toilet seat and cover removable, hinges stainless steel, with slow close,		002639

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.*