

Project:

Fixture Type:

Location:

Contact:

Wall mounted • Damp location listed PROGRESS LED

Description:

The Miter LED 34in linear bath bar highlights a beautiful layered effect to enhance a variety of interior areas. Each clear beveled glass panel is hand cut and positioned together, creating visual interest that extend to the corners. To complete the form, a back plate and linear accents frame the glass in a Brushed Nickel finish. Can be displayed horizontally or vertically. An integrated LED source provides a variety of energy and cost savings benefits.

Specifications:

- Brushed Nickel (-009) (plated)
- Steel Construction
- · Clear glass Beveled Panel, White glass diffuser
- The clear beveled glass panel is in front of a cased white mitered glass shade
- Linear accents frame the beveled glass
- The LED light is diffused to create an even glow.
- The backplate and straps are finished in Brushed Nickel
- · Its fashion-forward style complements Modern and Traditional interiors
- · Mount horizontally or vertically on the wall in bath and vanity settings to enhance a spa-like atmo-
- sphereMeasures 34in W x 5in ht.
- 53w integrated LED, 2,825 lumens 53 lumens/watt (delivered), 3000K color temperature, 90+ CRI.
- · ETL Safety listed for use in damp locations
- · Progress Lighting products are designed for exceptional quality, reliability, and functionality
- + Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting back plate for outlet box included
- 6" of wire supplied
- Meets California Title 24 JA8-2016

Performance:

| Number of Modules | 1 |
|------------------------|------------------------------------|
| Input Power | 53w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Delivered) | 2825/53 (LM-79) |
| ССТ | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 50,000 (L70/TM-21) |
| FCC | FCC Title 47, Part 15, Class B |
| Min. Start Temp | -30 °C |
| Warranty | 5 year limited warranty |
| Labels | cETLus Damp location listed |
| | Meets California Title 24 JA8-2016 |
| | |

P300153-009-30

Images:



Dimensions:

Width: 34" Depth: 3-7/8" Height: 5" H/CTR: 2-1/2313" (glass facing up)

Glass Width: 34-1/8" Height: 4-5/8"



Wall mounted • Damp location listed PROGRESS LED

P300153-009-30

Dimming Notes:

is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

| Lutron - NTELV-300 | | |
|--------------------------|--|--|
| Lutron - DVELV-300P | | |
| Lutron - Caseta Wireless | | |
| Leviton – 6672 | | |
| Leviton – 6674 | | |
| Lutron - AYCL-153P | | |
| Lutron - AYLV-600P | | |
| Lutron - MAELV-601 | | |
| Leviton - AWRMG-EAW | | |
| | | |

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.