

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination in residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more. **For commercial applications in which 24/7 use is required, use model FMLSL.**

CONSTRUCTION

Features a white acrylic diffuser and is available in 15" and 20" sizes. Hidden cam-latches provide easy diffuser removal for installation and maintenance.

OPTICS

15" units produce 2100 lumens, and 20" units produce 4000 lumens, all at 30,000 hours life.

ELECTRICAL

Fixture operates at 120 volts, 60 Hz.

15" Standard input = 30 watts, 70 lumens per watt.

20" Standard input = 44 watts, 90 lumens per watt.

Works with most standard incandescent dimmers (see list of suggested dimmers).

INSTALLATION

All mounting hardware included.

LISTINGS

cUL Certified to US and Canadian standards and listed suitable for damp locations.

WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Catalog Number
Notes
Type

Decorative Indoor

Residential LED
Low Profile Square



Flush Mount

HIGH-PERFORMANCE LED



Specifications			
	15"	20"	
Diameter:	14.75 (37.5)	20	(5.8)
Depth:	3.38 (8.6)	4	(10.2)
Weight:	1.5 lbs (.7 kg)	5 lbs	(2.3 kg)

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: FMLSDL 20 35840

Series		Module/CRI		Color temperature	
FMLSDL 15	15" Residential LED low profile square flush mount	218	>80	40	4000 K
FMLSDL 20	20" Residential LED low profile square flush mount	358	>80		

Residential LED Low Profile Square Flush Mount

SUGGESTED DIMMERS	
The FMLSDL is designed to operate with most standard Triac Based dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.	
Manufacturer	Part number(s)
Lutron	CT-600P/CT-603P
	DV-600P/DV-603P
	CTCL-153P
	DVCL-153P
	AYCL-153P
	DVELV-300P
Leviton	R50-IPL06
	6615-P
Pass & Seymour	HCL453PTCCCV6