

30 INCH GAS RANGE LRG3001U / LRG3001ULP



Product: 30 Inch Gas Range in Stainless Steel **Model Number:** LRG3001U / LRG3001ULP

TECHNICAL DETAILS		
Fuel Type	Natural Gas / LP Convertible	
Electrical Requirements	120V	
Circuit Breaker (A)	15 or 20A	
Frequency (Hz)	60 Hz	

BURNER PERFORMANCE

Total Burners	5
[1] Front Left (Single)	18,000 BTU
[2] Front Right (Single)	8,000 BTU
[3] Rear Left (Single)	4,000 BTU
[4] Rear Right (Single)	6,000 BTU
[5] Middle (Oval)	9,000 BTU
Tube Broil burner	10,000 BTU
U-shape burner (30" Oven)	18,500 BTU



FEATURES & BENEFITS

- High-Powered BTU Burners The high-powered 18,000 BTU burner provides fast, intense heat for creating large family meals and restaurant-quality dishes
- Large Oven Capacity 4.55 cu. ft. oven capacity can accommodate multiple dishes at a time
- Storage Space Storage drawer provides additonal storage space for cooking trays and other kitchen utensils
- Convection Fan Commercial convection fan provides controlled heat distribution for fast and efficient cooking
- Even Heat Broiler Reflective gas tube broiler distributes heat evenly to sear your food and seal in the juices
- Continuous Cast-Iron Grates Heavy-duty continuous cast-iron cooking grates that can handle any size cookware
- Professional Knobs Black burner control knobs add style to the bold range design
- Porcelain Spill Tray Single-piece black porcelain spill tray catches the mess and makes cleanup easy
- Porcelain Interior The gray porcelain oven interior adds a stylish touch and is easy to clean

ACCESSORIES (NOT INCLUDED)

Liquid Propane Gas Conversion Kit	LPKLRG3001U
Wok Ring	WK01
Cast Iron Reversible Griddle	RG1022

LIMITED WARRANTY: 24 MONTHS ON PARTS AND LABOR







PRODUCT DIMENSIONS		
Product Width	30"	
Product height (from bottom to top of back splash)	36 5/16"- 37 5/16"	
Product height (from bottom to top of side panel)	35 5/8"-36 5/8"	
Product depth (from back panel to bullnose)	28 5/16"	
Product depth (from back panel to control board)	27 3/4"	
Product depth (from back panel to side panel front)	24 3/4"	
Depth of control panel (minimum)	2 1/4"	
Depth of control panel (bullnose)	3 9/16"	
Adjustable Legs	Not to Exceed 1"	

REQUIRED CUTOUT SIZE

30 1/8" x 24 3/4" x 35 5/8 (+1")

