

FAMOWOOD®
GLAZE COAT®
PREMIUM
OUTDOOR
EPOXY



MEASURE • MIDA



MIX • MEZCLE



POUR • VIERTA

GLAZE COAT® PREMIUM OUTDOOR EPOXY is an elite-grade formula designed to withstand harsh conditions outside or in! NOW it's possible to create beautiful outdoor living spaces with projects that fit your sense of style. Enjoy the stunning, high-gloss finish on tables, lawn décor, patio kitchen designs and boundless other applications. Use on most any surface - wood, metal, glass, concrete, tile, ceramic and more. **Cures to a durable, smooth, crystal-clear protective finish.** UV rays are no match for Premium Outdoor Glaze Coat! The LOW VOC formula has excellent weather resistance and is waterproof, acid-free, scratch-resistant, and withstands temperatures up to 135 °F (57 °C intermittently).



Protect outdoor signs



Create high quality outdoor furniture



Display stained glass outdoors



Beautify and protect outdoor concrete projects



Protect and showcase canvas artwork outdoors

LEA Y SIGA LAS INSTRUCCIONES COMPLETAS (ADENTRO).
INFORMACIÓN DE PREPARACIÓN Y SOLICITUD:

- ¿Cuál es la profundidad máxima por aplicación? 1/4". Si el proyecto requiere un vertido más grueso / profundo, trabaje en capas de 1/4".
- ¿Se puede utilizar Glaze Coat Premium OUTDOOR en proyectos de interior? Si.
- ¿Se puede usar Glaze Coat PREMIUM OUTDOOR en pisos? NO
- ¿Se puede aplicar Glaze Coat PREMIUM OUTDOOR sobre tintes o recubrimientos a base de aceite? Si, siempre que aplique dos o más capas de poliuretano a base de agua sobre la superficie limpia.
- ¿Se necesitará más de una capa? Las superficies porosas o rugosas pueden requerir más de una capa. La aplicación de una fina capa de sellado suavizará la superficie y permitirá que el acabado de la capa de inundación más gruesa sea transparente como el cristal y sin burbujas. Tu cara.
- ¿Cuánto epoxy se necesitará para mi proyecto? Consulte el cuadro a continuación para conocer la cobertura total.

Tamaño de la Unidad	Cobertura a 1/16" de profundidad	Cobertura a 1/4" de profundidad
709 mL	0.44 m ²	0.11 m ²
2.8 L	1.78 m ²	0.44 m ²



Para obtener grandes ideas de proyecto, visite:
TRYGLAZE.COAT.COM
ECLECTICPRODUCTS.COM

⚠ ADVERTENCIA: Este producto puede exponerlo a sustancias químicas incluyendo metanol que según el Estado de California causa malformaciones congénitas y otros daños reproductivos. Para obtener más información, visite www.p65warnings.ca.gov. Cumple con ASTM D-4236.

GARANTÍA LIMITADA: El fabricante solo aceptará responsabilidad por el reemplazo del producto.

Manufactured by/Fabricado por Eclectic Products.
101 Dixie Mae Dr., Pineville, LA 71360-3993
USA/EE.UU. For technical assistance, call/Para obtener asistencia técnica, llame al (800) 767-4667. 8915069 22aw02

Create/strip in UPC-A
@ 100% GS1 Standard
0 14804 00011 1

FAMOWOOD®
GLAZE COAT®
PREMIUM
OUTDOOR
EPOXY

SUGGESTED SUPPLIES



FAMOWOOD®
GLAZE COAT®
HIGH GLOSS FINISH
PREMIUM
OUTDOOR
EPOXY
ACABADO DE ALTO BRILLO



24.0 fl oz (709 mL)



EXCELLENT
UV RESISTANCE



WEATHER
RESISTANT



CRYSTAL
CLEAR



LOW
ODOR



SCRATCH
RESISTANT

DANGER: THIS KIT CONTAINS ECH-BPA EPOXY RESIN, ECH-HBPA EPOXY RESIN, POLYETHERAMINE AND PACM THAT MAY BE HARMFUL IF MISUSED.

Read cautions on individual containers carefully. Keep out of reach of children.

PELIGRO: ESTE KIT CONTIENE RESINA EPOXI ECH-BPA, RESINA EPOXI ECH-HBPA, POLIETERAMINA Y PACM QUE PUEDEN SER NOCIVOS SI SE UTILIZAN MAL. Lea atentamente las precauciones en los recipientes individuales. Mantenga alejado del alcance de los niños.

GLAZE COAT - IT'S THE CLEAR CHOICE!™

READ AND FOLLOW COMPLETE INSTRUCTIONS (INSIDE).

PREP & APPLICATION INFO:

- What is the maximum depth per application? 1/4". If the project requires a thicker/deeper pour, work in layers of 1/4".
- Can Glaze Coat PREMIUM OUTDOOR be used on indoor projects? Yes.
- Can Glaze Coat PREMIUM OUTDOOR be used on floors? NO.
- Can Glaze Coat PREMIUM OUTDOOR be applied over oil-based stains or coatings? Yes, so long as you apply two or more coats of water-based polyurethane over the clean surface.
- Will more than one coat be needed? Porous or rough surfaces may require more than one coat. Applying a thin seal coat will smooth the surface and allow the finish of the thicker flood coat to be crystal clear and bubble-free.
- How much epoxy will be needed for my project? See below chart for total coverage.

Unit Size	Coverage at 1/16" deep	Coverage at 1/4" deep
24.0 fl oz	4.8 sq. ft.	1.2 sq. ft.
96.0 fl oz	19.2 sq. ft.	4.8 sq. ft.

For great project ideas, go to:
TRYGLAZE.COAT.COM
ECLECTICPRODUCTS.COM

⚠ WARNING: This product can expose you to chemicals including methanol which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov. Conforms to ASTM D-4236.

LIMITED WARRANTY: The manufacturer will not accept liability for more than product replacement.



†Based on varnish thickness of .8 mils and 1/16" Glaze Coat.
†Basado en un espesor de barniz de .8 mils y 1/16 mm Glaze Coat.

Product is to be applied in accordance with instructions and is not to be thinned or diluted.
VOC 72 g/L as Mixed

El producto debe aplicarse de acuerdo con las instrucciones y no debe rebajarse o diluirse.
COV 7.2 g/L según está mezclada