



1500 Cherokee Parkway, Suite 100, Acworth, GA 30102  
Phone: (706) 868-5451. Fax: (866) 816-6165  
www.acclaim-lighting.com

## IN11270

# INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

### CAUTION

**WARNING:** Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.  
Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### ASSEMBLY AND INSTALLATION

1. Attach nipple (10) to cross bar (7), and then secure it with a washer and a hex nut (9).
2. Attach the cross bar (7) to the outlet box (1) by using two box screws (8).
3. Secure the collar loop (12) to the nipple (10).
4. Secure the loop (15) onto the lamp body (16).
5. Connect one end of the chain to the collar loop (12) using a chain lock (13).  
Connect another end of the chain to the loop (15) using another chain lock.
6. Pass fixture wire and ground wire through chain links no more than 3 inches apart, then pass wires through collar, canopy (11), collar loop (12), nipple (10), and into outlet box (1).
7. Pull out the outlet wire and ground wire from the outlet box (1). Make wire connections (5).
  - Ribbed wire (w/o marking) from light to White wire (2) from power source
  - Smooth wire (w/o marking) from light to Black wire (3) from power source
  - Loop the ground wire (4) to cross bar (7) with a ground screw (6)
8. Attach the canopy (11) to the cross bar (7), insert the collar loop (12) through the hole, and then secure it by tightening collar.
9. Attach the glass shades (18) to socket (19) and secure them with socket rings (17).
10. Screw the bulbs (not included) into the sockets (19).

