

PLEASE KEEP AWAY FROM COMBUSTIBLE MATERIALS.

into place. D. Center of socket must not be closer than 1 1/2" to closed ends (wall surfaces and partitions).

C. Press socket straight down into track and cable until socket snaps

Installation And Safety Instructions

Be sure the electricity to the system you are working on is turned off;

Use of other manufacturers components will void warranty, listing and

and File This Sheet For Future Reference. ITEM#

either the fuse removed or the circuit breaker set at off.

IMPORTANT SAFETY INSTRUCTIONS

Please keep away from combustible materials.

create a potential safety hazard.

TO INSTALL 9428 SOCKET

Save these instructions.

Use only with Ambiance® 105° Cable.


B. Install bulbs (not included), 5 watt maximum.

Line art shown may not exactly match the fixture enclosed. However, the installation instructions do apply to this fixture. Fill in Item Number on Carton

- REFLECTORS *CABLE ***TRACK 9428 SOCKET *NOT INCLUDED**
- A. Determine socket location and spacing, minimum 4" center to center. **B.** Install bulbs (not included), 5 watt maximum.

Save these instructions.

- C. Press socket straight down into track and cable until socket snaps
- D. Center of socket must not be closer than 1 1/2" to closed ends (wall surfaces and partitions).
- REFLECTORS *CABLE ***TRACK 9428 SOCKET *NOT INCLUDED**



TO INSTALL 9428 SOCKET

Use only with Ambiance® 105° Cable.


- CAUTION:Do not remove reflectors, heat from lamps will damage cable.
- A. Determine socket location and spacing, minimum 4" center to center.
- into place.

- Use of other manufacturers components will void warranty, listing and create a potential safety hazard.

Please keep away from combustible materials.

- either the fuse removed or the circuit breaker set at off.

- Be sure the electricity to the system you are working on is turned off;



and File This Sheet For Future Reference. ITEM# **IMPORTANT SAFETY INSTRUCTIONS**



LAMP SELECTION AND SPACING GUIDE

5'420	56	5,000	6.5	4-15	6279	XSAT		0
5,300	53	000'6	0'7	4-15	8278	XSAT		0
2,400	91	000'61	7.2	4-15	NON3X 1824	АССЕИТ		0
5,200	8	50,000	2.1	6-12	7279	АССЕИТ		0
(IEWE K) COFOE YE EKOX	AP FROX LIGI (UMEN)	(HONKE Ç L'EE RYTEI	OON2 (MEI M≒LÆ	(LICHEZ SBYCIN SCECEZEI	C FIALOC	APPLETON LIGHT:		K) DE DX
	ATAQ				-	-		
LAMP SELECTION AND SPACING GUIDE								
							•	-

4-15

XENON

9732

XSAT

022503


information recalculated at approximately 12 volts. Lamp data is based on manufacturers published

2.P

XENON 5,555 33 000'8 2't 4-15 9732 **TASK** 5,450 2,000 3'6 **XSAT 5** 21-4 6779 5,300 000'6 **0. XSAT** 23 21-4 8276 **XENON** 19,000 5,400 **9**L 7.2 4-12 1576 ACCENT 5,200 50,000 ACCENT 8 r.s 6-12 7279 (INCHE C (IEWE (NEWIT) HOURES NUMBER APPLICATION

LIGHT

information recalculated at approximately 12 volts. Lamp data is based on manufacturers published



5,555

sea gu**l lig**hting.

HC-128

33

000'8