

## 3. Ventilation and installation

- To ensure adequate ventilation for your refrigerator or freezer see recommended cabinetry dimensions below.
- If building the appliance into a cupboard, follow installation instructions provided with the integration kits.

Product dimensions	RF135B		RF170W		RF170A	
	inches	mm	inches	mm	inches	mm
A Overall height of product	67 1/2	1715	67 1/2	1715	67 1/2	1715
B Overall width of product	25	635	31 1/8	790	31 1/8	790
C Overall depth of product (excludes handle, includes evaporator)	27 3/8	695	27 3/8	695	27 3/8	695
Cabinetry dimensions (including minimum air clearances)						
D Inside height of cavity	68 3/8	1735	68 3/8	1735	68 3/8	1735
Flush with refrigerator chassis – full door rotation						
E Inside width	26 1/2	675	32 3/4	830	32 3/4	830
F Inside depth	24 3/8	620	24 3/8	620	24 3/8	620
Flush with refrigerator door – full door rotation						
G Inside width	31 1/8	790	37 1/4	945	41 3/8	1060
H Inside depth flush to flat door	27 3/8	695	27 3/8	695	27 3/8	695
Flush with refrigerator door – 90° door rotation (for full drawer/shelf access, the doors need to be open past 90°)						
I Inside width	29 3/8	745	35 3/8	900	40	1015
J Inside depth flush to flat door	27 3/8	695	27 3/8	695	27 3/8	695
Minimum clearances						
K Side clearance	3/8	20	3/8	20	3/8	20
L Side clearance – hinge side flush with door – full rotation	5 5/16	135	5 5/16	135	5 5/16	135
M Side clearance – hinge side flush with door – 90° rotation	3 1/2	90	3 1/2	90	3 1/2	90
N Rear clearance (incl. evaporator tray)	1 1/8	30	1 1/8	30	1 1/8	30
O Vent – around top of cupboard (optional)	2	50	2	50	2	50
P Top clearance – above refrigerator cabinet	2	50	2	50	2	50
Q Door clearance – hinge side flush with chassis – full rotation	25 3/8	645	25 3/8	645	12 3/4	325
R Door clearance – hinge side flush with door – full rotation	20 3/8	530	20 3/8	530	8 1/4	210