

CLEAR HIGH GLOSS TOP COAT • LOW ODOR

From the inventors of fluorescent color, DayGlo Screamin' Fluorescent Paint is a premium, low odor fluorescent water-based paint. DayGlo Filteray® W Clear Overcoat is a high gloss top coat for use with DayGlo Screamin' Fluorescent Paints. DayGlo Filteray® W Clear Overcoat is used to protect the paints when they are used in outdoor applications. Filteray® W Clear Overcoat contains UV absorbers and is designed as a glossy protective coating for DayGlo Screamin' Fluorescent Paints. Filteray® W Clear Overcoat can double the lightfastness of DayGlo Screamin' Fluorescent Paints. However, DayGlo Filteray® W is not recommended for interior use where exposed to black light—fluorescent surfaces coated with DayGlo Filteray® W will not fluoresce in the dark under black light.

General Application Instructions:

1. Please allow DayGlo Screamin' Fluorescent Paints undercoat to dry for at least 24 hours before applying DayGlo Filteray® W Clear Overcoat.
 2. Apply one moderate coat of DayGlo Filteray® W Clear Overcoat. Thin only if necessary, using water.
 3. Allow 2 hours to dry before putting into service.
 4. Clean brushes should always be used. After use, they can be cleaned up with warm water.
- Application of DayGlo Filteray® W Clear Overcoat will cause the color to deepen. It will have a glossy finish. Fluorescent surfaces coated with DayGlo Filteray® W will not fluoresce in the dark under black light.
 - DayGlo Screamin' Fluorescent Paints and DayGlo Filteray® W Clear Overcoat may be applied with a spray gun. Stir well and thin to spraying consistency using water, then strain.
 - The normal shelf life of DayGlo Screamin' Fluorescent Paints and DayGlo Filteray® W Clear Overcoat is 1 year in unopened cans. These products should be stirred before use.
 - Avoid freezing and close can tightly when not in use. Use with adequate ventilation.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**CAUTION: KEEP OUT OF REACH OF CHILDREN.
PROTECT FROM FREEZING.**

PRECAUTIONS: Avoid skin and eye contact. Wash hands immediately after use. When using, use impermeable work gloves. Wear a work apron. Do not take internally. If swallowed, get medical attention immediately. MAY CAUSE EYE AND SKIN IRRITATION. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes; get medical attention. For emergency, call your physician, local poison control center or local emergency room. For product health information, call 1-800-424-9300.

Disclaimer: Our technical advice, information and statements—given verbally, in writing or in the form of test results—is offered for your guidance without warranty. **NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.** This also applies where protective rights of third parties are involved. It does not release the user from the obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our products.

CALIFORNIA PROP 65: This product contains components known to the state of California to cause cancer: Cumene (98-82-8) and Ethylbenzene (100-41-4) and birth defects or other reproductive harm: Toluene (108-88-3).



DayGlo

DayGlo Color Corp.
4515 St. Clair Avenue
Cleveland, OH 44103 USA
(216) 391-7070 www.DayGlo.com

