

QUIETWALK®

PREMIUM ACOUSTIC UNDERLAYMENT

PRODUCT GUIDE

CAN BE USED OVER CONCRETE,
WOOD SUBFLOORS & INFLOOR
HEATING SYSTEMS



Material	Recycled Fibers	Recycled Fibers	Recycled Fibers	Recycled Fibers
Approved Subfloor	Wood, Concrete, Gypsum Concrete and Cement Backer Units	Wood, Concrete, Gypsum Concrete and Cement Backer Units	Wood, Concrete, Gypsum Concrete and Cement Backer Units	Wood, Concrete, Gypsum Concrete and Cement Backer Units
Laminate Floors	X	X	X	
Floating Engineered Wood	X	X	X	
Nail-Down Engineered Wood			X	X
Glue-Down Engineered Wood	X		X	X
Glue-Down Wood	X		X	X
Nail-Down Wood			X	X
Floating Engineered/Rigid Core Vinyl Plank (EVP)			X	
Glue Down Engineered Vinyl Plank (EVP)			X	
Glue Down Wood/Plastic Composite (WPC)			X	
Floating Wood/Plastic Composite (WPC)			X	
Floating Luxury Vinyl Plank			X	
Glue Down Luxury Vinyl Tile or Plank			X	
Mohawk Fast Tile			X	
Tile or Stone				
SOUND RATINGS				
IIC Sound Rating - Impact Vibration Sounds	71	71	70	60
STC Sound Rating	66	66	62	50
Delta IIC Sound Rating	24	24	28	20
R-Value	0.58	0.58	0.53	0.57
Moisture Emissions Protection	7 lbs per 1000 sq ft per day	5 lbs per 1000 sq ft per day	6 lbs per 1000 sq ft per day	No Moisture Barrier
Water Vapor Transmission Rate	1.87 lbs / 1000 sq ft / 24 hrs	1.4 lbs / 1000 sq ft / 24 hrs	1.31 lbs / 1000 sq ft / 24 hrs	No Moisture Barrier