# FRSC Chemical Solutions

# SAFETY DATA SHEET

### 1. Identification

Product identifier Gunk Carburetor Parts Cleaner - Non Chlorinated

Other means of identification

SDS number M4815NC

**Part No.** M4815NC, M4819NC

**Tariff code** 3814.00.1000

Recommended use Carburetor Cleaner

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name
Address
RSC Chemical Solutions
600 Radiator Road
Indian Trail, NC 28079

**United States** 

**Telephone** Customer Service: (704) 821-7643

Technical: (704) 821-7643

Website www.rscbrands.com
E-mail sds@rscbrands.com

**Emergency phone number** Emergency Telephone: (303) 623-5716

Emergency Contact: RMPDC (877-740-5015)

# 2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Carcinogenicity Category 2
Reproductive toxicity Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1
Hazardous to the aquatic environment, acute Category 3

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement**Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting

Category 2

effects.

#### **Precautionary statement**

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before

#### Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

#### **Disposal**

None known.

#### Hazard(s) not otherwise classified (HNOC)

Supplemental information

19% of the mixture consists of component(s) of unknown acute oral toxicity. 19% of the mixture consists of component(s) of unknown acute dermal toxicity. 12% of the mixture consists of component(s) of unknown acute inhalation toxicity. 91% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 79% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

Dispose of contents/container in accordance with local/regional/national/international regulations.

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
2-PROPANONE		67-64-1	70 - < 80
Distillates (petroleum), Hydrotreated Light		64742-47-8	10 - < 20
BENZENE, DIMETHYL		1330-20-7	5 - < 10
Carbon Dioxide		124-38-9	5 - < 10
ETHYLBENZENE		100-41-4	3 - < 5

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

> Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Ingestion

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Material name: Gunk Carburetor Parts Cleaner - Non Chlorinated

M4815NC, M4819NC Version #: 03 Revision date: 10-15-2018 Issue date: 05-06-2015

Components	Contaminants (29 CFR 1910.1000) Type	Value	
2-PROPANONE (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
BENZENE, DIMETHYL (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Distillates (petroleum), Hydrotreated Light (CAS 34742-47-8)	PEL	400 mg/m3	
,		100 ppm	
ETHYLBENZENE (CAS	PEL	435 mg/m3	
100-41-4)		100 ppm	
JS. ACGIH Threshold Limit Values			
Components	Туре	Value	
2-PROPANONE (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
BENZENE, DIMETHYL CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
US. NIOSH: Pocket Guide to Chemic			
Components	Туре	Value	
2-PROPANONE (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
	STEL	655 mg/m3	
		150 ppm	
	STEL	-	
		150 ppm	
(CAS 1330-20-7)  Carbon Dioxide (CAS		150 ppm 435 mg/m3	
(CAS 1330-20-7)  Carbon Dioxide (CAS	TWA STEL	150 ppm 435 mg/m3 100 ppm	
(CAS 1330-20-7)  Carbon Dioxide (CAS	TWA	150 ppm 435 mg/m3 100 ppm 54000 mg/m3	
(CAS 1330-20-7)  Carbon Dioxide (CAS	TWA STEL	150 ppm 435 mg/m3 100 ppm 54000 mg/m3 30000 ppm	
(CAS 1330-20-7)  Carbon Dioxide (CAS 124-38-9)  ETHYLBENZENE (CAS	TWA STEL	150 ppm 435 mg/m3 100 ppm 54000 mg/m3 30000 ppm 9000 mg/m3	
CAS 1330-20-7)  Carbon Dioxide (CAS 124-38-9)  ETHYLBENZENE (CAS	TWA STEL TWA	150 ppm 435 mg/m3 100 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm	
BENZENE, DIMETHYL (CAS 1330-20-7)  Carbon Dioxide (CAS 124-38-9)  ETHYLBENZENE (CAS 100-41-4)	TWA STEL TWA	150 ppm 435 mg/m3 100 ppm 54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm 545 mg/m3	

#### **Biological limit values**

<b>ACGIH</b>	<b>Biological</b>	Exposure	Indices
ACGIII	Diviouicai	LADOSUIC	IIIUICES

Components	Value	Determinant	Specimen	Sampling Time	
2-PROPANONE (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
BENZENE, DIMETHYL (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*	
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece. Applicable for industrial

settings only.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Applicable for industrial settings only.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Applicable for industrial settings only.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with

organic vapor cartridge and full facepiece if threshold limits are exceeded. Applicable for industrial

settings only.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

Appearance Clear. Liquid

Physical state Liquid.
Form Aerosol.
Color Colorless
Odor Solvent.odor
Odor threshold Not available.
pH Not available.

Melting point/freezing point -138.46 °F (-94.7 °C) estimated

Initial boiling point and boiling

range

133 °F (56.11 °C)

-20.0 °F (-28.9 °C) Pensky-Martens Closed Cup

Evaporation rate > 1 BuAc

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flash point

0.7 % estimated

Flammability limit - upper

(%)

12.8 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 4877.35 hPa estimated

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

869 °F (465 °C) estimated Auto-ignition temperature

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

6.67 lbs/gal Density **Explosive properties** Not explosive. Heat of combustion (NFPA 27.4 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Percent volatile 100 % 8.0 Specific gravity

VOC < 10 % w/w

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents. Aluminum. Halogens.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

#### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Components	Species	Test Results	
2-PROPANONE (CAS 67-64-1)			
<b>Acute</b>			
Dermal			
LD50	Rabbit	20000 mg/kg	
Inhalation			

LC50 Rat 50.1 mg/l, 8 Hours

Oral

LD50 Rat 5800 mg/kg

Material name: Gunk Carburetor Parts Cleaner - Non Chlorinated

SDS US

Components Species Test Results

BENZENE, DIMETHYL (CAS 1330-20-7)

Acute Dermal

LD50 Rabbit > 43 g/kg

Inhalation

LC50 Rat 6350 mg/l, 4 Hours

Oral

LD50 Rat 3523 - 8600 mg/kg

ETHYLBENZENE (CAS 100-41-4)

Acute Dermal

LD50 Rabbit 17800 mg/kg

Oral

LD50 Rat 3500 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, DIMETHYL (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

ETHYLBENZENE (CAS 100-41-4) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in

laboratory animals. Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

# 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
2-PROPANONE (CAS	67-64-1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
BENZENE, DIMETHYL	(CAS 1330-20-7)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

SDS US

M4815NC, M4819NC Version #: 03 Revision date: 10-15-2018 Issue date: 05-06-2015

Components **Species Test Results** 

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours Crustacea Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

ETHYLBENZENE (CAS 100-41-4)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours LC50 Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours Fish

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-PROPANONE -0.24 BENZENE. DIMETHYL 3.12 - 3.2**ETHYLBENZENE** 3.15

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

> under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If

discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

D001: Waste Flammable material with a flash point <140 F Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

**UN** number Not available.

**UN proper shipping name** 

Consumer Commodity

Transport hazard class(es)

ORM-D

Subsidiary risk

Not available. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** T75, TP5 306 Packaging exceptions 304 Packaging non bulk 314, 315 Packaging bulk

IATA

**UN number** UN1950

**UN proper shipping name** Aerosol, flammable

Transport hazard class(es)

2.1 Class Subsidiary risk

Not available. Packing group

**Environmental hazards** No. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN1950 **UN** number **UN** proper shipping name Aerosols

Transport hazard class(es) Class 2 Subsidiary risk

Packing group Not available.

**Environmental hazards** 

Marine pollutant No. **EmS** F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code IATA; IMDG



## 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations** 

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-PROPANONE (CAS 67-64-1) Listed. BENZENE, DIMETHYL (CAS 1330-20-7) Listed. ETHYLBENZENE (CAS 100-41-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No (Exempt)

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
BENZENE, DIMETHYL	1330-20-7	5 - < 10	
ETHYLBENZENE	100-41-4	3 - < 5	

# Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE, DIMETHYL (CAS 1330-20-7) ETHYLBENZENE (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

# Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

2-PROPANONE (CAS 67-64-1)

6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

2-PROPANONE (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

2-PROPANONE (CAS 67-64-1) 6532

# FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

2-PROPANONE (CAS 67-64-1) Low priority

# **US state regulations**

#### **California Proposition 65**



WARNING: This product can expose you to ETHYLBENZENE, which is known to the State of California to

cause cancer. For more information go to www.P65Warnings.ca.gov.

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-PROPANONE (CAS 67-64-1)

BENZENE, DIMETHYL (CAS 1330-20-7) ETHYLBENZENE (CAS 100-41-4)

#### **International Inventories**

**Philippines** 

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

Philippine Inventory of Chemicals and Chemical Substances

# 16. Other information, including date of preparation or last revision

 Issue date
 05-06-2015

 Revision date
 10-15-2018

Version # 03

HMIS® ratings Health: 3\*

Flammability: 4 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 4 Instability: 0

NFPA ratings



Material name: Gunk Carburetor Parts Cleaner - Non Chlorinated

SDS US

Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **Revision information**

This document has undergone significant changes and should be reviewed in its entirety.