

Why choose CovRguard®?



LONG-LASTING AND ENERGY EFFICIENT

Rated to last 20,000-30,000 hours.



SHATTER-RESISTANT

Shield contains broken glass if the bulb is broken. Ideal for use in food industry, hospitality, schools, and healthcare facilities.



COMPLIANT

Meets the requirements for lamps in Regulated Food establishments.

Lowe's Item #	Model #	Bulb Shape	Base Description	Length	Watts	Rated Life	Color Temp	Lumens
Ecolux CovRguard®								
1484848	73194	T5	G5	24 in	14	30,000 hours	3000 K	1200
1484929	81547	T5	G5	48 in	28	30,000 hours	3500 K	2672
1484868	25768	T5	Medium Bi-Pin	48 in	28	20,000 hours	5000 K	1940
1484860	15975	T8	Medium Bi-Pin	24 in	17	30,000 hours	3500 K	1242
Ecolux Starcoat CovRguard®								
1484862	15976	T8	Medium Bi-Pin	24 in	17	30,000 hours	4100 K	1242
1484969	15981	T8	Medium Bi-Pin	36 in	25	30,000 hours	3500 K	1920
1483661	15990	T8	Medium Bi-Pin	36 in	25	30,000 hours	3500 K	1970
1483668	41125	T8	Medium Bi-Pin	48 in	32	30,000 hours	3000 K	2715
1483680	41127	T8	Medium Bi-Pin	48 in	32	30,000 hours	4100 K	2715
1483693	47351	T8	Medium Bi-Pin	48 in	40	20,000 hours	4100 K	3250
High Output CovRguard®								
1484891	70994	T5	G5	36 in	39	30,000 hours	3500 K	3230
1484879	48436	T5	G5	48 in	54	30,000 hours	3500 K	4560
1484863	48458	T5	G5	48 in	54	30,000 hours	4100 K	4560
1484822	80311	T5	G5	48 in	54	30,000 hours	5000 K	4370
High Output Watt-Miser CovRguard®								
1484977	65107	T5	G5	48 in	47	30,000 hours	5000 K	4167
CovRguard®								
953445	32775	T8	Medium Bi-Pin	48 in	32	30,000 hours	4100 K	2800

GE is Here to Help

GE Lowe's Support: **1-855-GE4Lowe's** (1-855-434-56937) or
LTG.LoweSOS@GE.com | Hours: 8:00am-8:00pm EST

Over 1,000 Products Online