



QC CL-1500 Specifications

| Air Flow | 1,472 CFM |
|--|---|
| HVI-916 Airflow (for CA Title 24 New Construction) | 1,100 CFM |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT | Covers 491 SQFT to 736 SQFT |
| Energy Use | 117 Watts |
| Amps | 1.21 |
| Motor Voltage | 120 VAC, 60 Hz |
| # of Speeds | 1 |
| dBA | Hi: 37.4 |
| Minimum Attic Clearance | 32" |
| Duct Diameter | 14" |
| Duct Length | 6 feet |
| Motor Head Diameter | 14 1/2" |
| Motor Head Length | 13 1/2" |
| Dampers | Barometric Pressurized R5 Dampers |
| Controls | Recommended: IT-36002 QuietCool RF Wireless |
| | Control Kit |
| Warranty | 10 Years |
| Framing | None Required |
| Joist Cutting | None Required; fits 16" or 24" on center |
| Minimum Suggested Attic Venting | 1.97 SQ FT net free area |
| Ceiling Rough Opening | 14 1/4" × 14 1/4" |
| Removable Grille Outside Dimension | 16" x 16" |
| Shipping Weight | 40 lbs. |
| Box Dimensions | 20" × 20" × 38" |
| In The Box | -QC CL-1500 Motorhead -Damper Box |
| | -Ceiling Grille -6 Foot Duct |
| | -Cut-out Template -Accessory Bag |
| | -Window Locks |





