## **INSTALLATION INSTRUCTIONS**

# **Installation Manual**

IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

settings are indicated by words ("cold", "warm", "bot" mbers, or graphically.

> y change in matcelal, of any exidence of talles of this listing.

consist no marked risk the model number or, in the case of private mark as well as the model number or, in the case of private on the name, trademark, or mark of the customer for whom the g was manufactured as well as the model number.

(ANS)

UPC

Product:

Lasued To

С

CT OUT INCLUDES

Plumbing Fixture Fittings

Kaiping Neart Cartridge Co., Ltd. No. 28 Neihuan Dong Read, Shuikou Town, Kaiping City, GUANDONG China

Charles Music Contractor Charles Charles Charles

File No. 8737



David Martingen Run Chaney Chairman Product Certification Confine

> own above. Any change in material, ion Committee, or any evidence of ause for revocation of bis listing, if LDMD Research and Testing, loc.



## **INSTALLATION STEPS**

This product has been inspected and



### Instruction of use

 Turn on the 10 faucet handle, lift the handle and turn it up and down to adjust the temperature of the hot and cold water. (Top cold and hot bottom)
 Turn 11 (12) (13) to turn on and adjust the water outlet mode, and follow the icons above switch to Rain shower head, Hand shower and faucet outlet.
 After using, remember to turn off the 10 faucet handle.

### **CLEANING CARE**

In order to keep the appearance of faucet clean, bright and good performance, please take care of the faucet as follows;

- 1. Rinse with water only and dry with soff cotton cloth;
- 2.Use mild liquid and colorless glass cleaner to remove surface dirt and scale film, or use polish without abrasive effect;
- 3.Do not use abrasive deterfgent, polish, emery cloth, paper towel or scraper, etc.;

4.Do not use acid cleaner, or cleaner and soap with insoluble gran etc.;

5.In the process of use, mud my accumulate in the bubbler and make the water flow show, The bubbler can be unscrewed, rinsed with water, and then installed back in place.

Please feel free to contact us if you have any questions. We will help to solve the issue together with you. OUR EMAIL: services@rbrohant.com



#### installation steps

1. Drain the sewage from the hot and cold water pipes first.

2. Install the faucet ① in place, connect ② and ③, and then insert it into ① to check whether it is in place. Place ③ close to the wall, determine the fixed point, make a mark, and then drill the hole.

3. Insert ④ into ②, then fix ②, ③, ④ on the wall at the same time, and check whether the installation is stable.
4. Finally, fix ⑥ in an appropriate position, then connect ⑧ to ①, and then connect ⑦ to ⑧. Then connect ⑤ to ④. Note that the rubber pads of all connecting parts must be installed in place.

5. Finally, test the water to check whether the connecting parts are leaking. So far, the entire shower is installed.

