

P5187

Ceiling stem mounted • Dry location listed



Description:

Uniquely shaped modern LED mini-pendant with sleek lines. This pendant utilizes a Brushed Nickel Finish with a white linen interior for optimal light output.

Specifications:

Brushed Nickel (-09) (plated)
Steel construction
metal
Dimmable (See Dimming Notes)
Canopy covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
10 feet of wire supplied
ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	121171.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	
Warranty	5 year warranty
Labels	cCSAus Dry location listed ENERGY STAR® qualified

P5187-0930K9

Images:



Dimensions:

Diameter: 10"
Height: 10-3/4"
Overall Ht. W/Stem: 77"

P5187-0930K9

Dimming Notes:

P5187-0930K9 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron DVELV-300P

Lutron NTELV-300

Lutron VTELV-600

Lutron MAELV-600

Lutron SPELV-600

Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.