# **Boyel Living**

Webs: www.boyelliving.com

Tel: (833)998-6986 (323)982-8955

Email: service@boyelliving.com

## **PULL-DOWN KITCHEN FAUCET** INSTALLATION INSTRUCTIONS

#### Notes before installation:

- 1.Please check that all components are present.
- 2.Before installation ensure that all feed lines are clear of debris and on/off valve is present.
- 3.Ensure water pressure is between 20-125 PSI (includes combination 3.DO NOT use caustic cleaning products as the use will break down of hot and cold feed lines).
- 4. Pictures in the manual are general in content and may not represent exactly your purchased faucet. If you are having difficulties please contact us.
- 5. If you will be away from home for an extended period you should shut off the main water supply.

#### Daily maintenance:

- 1. Use a soft cloth and vinegar to remove hard-water spots.
- 2.Check aerator(if present) regularly for calcium build up When water stream is not optimum.
- finish and will void the product warranty.
- 4. Acceptable cleaners include vinegar or mild non-abrasive liquid deteraents.
- 5. If the water pressure appears to be less than optimum remove, inspect, clean or replace aerator.


### Tools we will need:




Adjustable Wrench



Philips Screwdriver




1. Remove the rubber washer, metal washer and locking nut from the faucet and glass rinser. Install faucet and glass rinser through center hole.



2.Re-install the rubber washer followed by the metal washer and lock-nut. Hand tighten then tighten further using a screw driver to tighten lock-nut screws.



3. Attach the pull-down hose to the outlet tube



4.Install the weight ball to pull-down hose in place





6.Remove the sprayer head and turn on faucet for 1-minute to flush debris. Close the handle and re-assemble spray head.

Note: Pictures in the manual are general in content and may not represent exactly yourpurchased faucet. If you are having difficulties please contact us.